



# **COLD DISPENSED BEVERAGE EQUIPMENT**







## High Intensity® Mixing

Because viscosity or thickness of concentrate can vary widely, BUNN has developed the High Intensity mixing chamber to assure best results in every cup with great-tasting, authentic juice flavor.

The concentrate is injected along with water under high pressure into the mixing chamber and is then thoroughly blended to create a quality finished beverage. High-viscosity concentrate at ratios of 4-to-1 and 5-to-1 (water-to-concentrate) can be mixed accurately and consistently. This assures a high-quality, delicious beverage of ideal consistency from the top to the bottom of every glass.

# Juice – JDF Segmented Door

*Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design*

New segmented LED lighted door features different display slots and eight different graphics allowing for easy adaptability to beverage menu

One dispenser delivers both frozen and ambient products increasing profits by lowering costs

Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 and 5+1 high viscosity concentrates accurately and consistently

Push and Hold and Portion Control models, (Push and Hold can also be set for a single size portion dispense)

JDF-2S Burst Capacity: At rate of one 12 oz drink/min, 70 drinks before exceeding 41°F (75°F ambient and 75°F incoming water temp)

JDF-4S Burst Capacity: at rate of three 12 oz (355ml) drinks/min, 145 drinks before exceeding 41°F (75°F ambient and 75°F incoming water temp)



JDF-4S PC  
(Segmented Lit Door)



JDF-2S PB  
(Segmented Lit Door)

## Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION									ELECTRICAL
Product #	Model	Lighted Display	Portion Control	Remote Switches	Cold Water Dispense	Dimensions Height x Width x Depth (Inches)			Volts
<a href="#">37300.0079</a>	JDF-4S PB	YES	NO	NO	NO	33.40	15.70	27.50	120
<a href="#">37300.0080</a>	JDF-4S PC	YES	YES	NO	NO	33.40	15.70	27.50	120
<a href="#">37900.0061</a>	JDF-2S PB	NO	NO	NO	NO	33.40	10.50	27.00	120
<a href="#">37900.0063</a>	JDF-2S PB	YES	NO	NO	NO	33.40	10.50	27.00	120
<a href="#">37900.0064</a>	JDF-2S PC	YES	YES	NO	NO	33.40	10.50	27.00	120
<a href="#">37900.0070</a>	JDF-2S w/LOCK	NO	NO	NO	NO	33.40	10.50	27.00	120
<a href="#">37900.0071</a>	JDF-2S w/LOCK	YES	NO	NO	NO	33.40	10.50	27.00	120
<a href="#">37900.0072</a>	JDF-2S w/LOCK	YES	YES	NO	NO	33.40	10.50	27.00	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.





# Juice – JDF-2S

*Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design*

One dispenser delivers both frozen and ambient products increasing profits by lowering costs

Superior brix accuracy and burst capacity ensure consistent drinks throughout the day

Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 and 5+1 high viscosity concentrates accurately and consistently

Push and Hold and Portion Control models, (Push and Hold can also be reset for a single size portion dispense)

Burst Capacity: at rate of one 12 oz drink/min, 70 drinks before exceeding 41°F (75°F ambient and 75°F incoming water temp)



JDF-2S PC LD  
(Lighted door with portion control)



JDF-2S PB LD  
(with remote switches)



JDF-2S  
(with cold water dispensed)



JDF-2S LD

## Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION									ELECTRICAL
Product #	Model	Lighted Display	Portion Control	Remote Switches	Dual Dispense*	Dimensions Height x Width x Depth (Inches)			Volts
37900.0001	JDF-2S	NO	NO	NO	NO	33.40	10.50	27.00	120
37900.0008	JDF-2S LD	YES	NO	NO	NO	33.40	10.50	27.00	120
37900.0025	JDF-2S	NO	NO	NO	YES	33.40	10.50	27.00	120
37900.0044	JDF-2S LD	YES	NO	YES	NO	33.40	10.50	27.00	120
37900.0016	JDF-2S PC LD	YES	YES	NO	NO	33.40	10.50	27.00	120

\*Equipment will dispense via multiple nozzles simultaneously



# Juice – JDF-4S

*Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design*

One dispenser delivers both frozen and ambient products increasing profits by lowering costs

Superior brix accuracy and burst capacity ensure consistent drinks throughout the day

Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 and 5+1 high viscosity concentrates accurately and consistently

Push and Hold and Portion Control models, (Push and Hold can also be reset for a single size portion dispense)

Burst Capacity: at rate of three 12 oz drinks/min, 145 drinks before exceeding 41°F (75°F ambient and 75°F incoming water temp)



JDF-4S PC LD  
(Lighted door with portion control)



JDF-4S



JDF-4S LD  
(Lighted door with cold water dispensed)

## Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION							ELECTRICAL		
Product #	Model	Lighted Display	Portion Control	Remote Switches	Cold Water Dispense	Dimensions Height x Width x Depth (Inches)	Volts		
37300.0000	JDF-4S	NO	NO	NO	NO	33.40 x 15.70 x 27.50	120		
37300.0002	JDF-4S	NO	NO	NO	YES	33.40 x 15.70 x 27.50	120		
37300.0004	JDF-4S LD	YES	NO	NO	NO	33.40 x 15.70 x 27.50	120		
37300.0006	JDF-4S LD	YES	NO	NO	YES	33.40 x 15.70 x 27.50	120		
37300.0023	JDF-4S PC LD	YES	YES	NO	NO	33.40 x 15.70 x 27.50	120		
37300.0054	JDF-4S LD	YES	NO	YES	NO	33.40 x 15.70 x 27.50	120		
37300.0083	JDF-4S COASTAL	YES	NO	NO	NO	33.40 x 15.70 x 27.50	120		

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.







CORPORATE HEADQUARTERS

5020 Ash Grove Drive, Springfield, IL USA 62711  
(+1) 217-529-6601 • 800-637-8606



[www.bunn.com](http://www.bunn.com)