



DISPENSED WATER EQUIPMENT



A clear glass mug filled with water, showing condensation on the rim, sits on a dark wooden surface. The image is overlaid with a pattern of dark blue and light grey diamond shapes. The text "HOT WATER" is centered on the mug in white capital letters.

HOT
WATER

Precision Temperature *Medium Volume*

- 3gal (11.4L) tank
- Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)
- Contemporary, low profile design for front-of-house and self-service
- Thinsulate® tank insulation provides increased energy efficiency
- LED display provides simple temperature adjustment
- Drip tray included



H3X Element

Prop 65 Warning for California Residents
This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION								CAPACITY		ELECTRICAL
								WATER INPUT 60°F / 15.5°C		
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			gal/hr	L/hr	Volts
			°F	°C						
45300.0006	H3X	STAINLESS	212	100	22.30	7.60	20.48	5.5	17.8	120
45300.0007	H3X	STAINLESS	212	100	22.30	7.60	20.48	9.8	31.8	208
45300.0008	H3X	STAINLESS	212	100	22.30	7.60	20.48	4.1	13.2	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Precision Temperature *Medium Volume*

5gal (18.9L) tank

Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)

LED display provides simple temperature adjustment



H5X Element
(Black)



H5X Element
(Stainless)

Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION								CAPACITY		ELECTRICAL
								WATER INPUT 60°F / 15.5°C		
Product #	Model	Finish	Temperature Setting		Dimensions			gal/hr	L/hr	Volts
			°F	°C	Height x Width x Depth (Inches)					
43600.0002	H5X	STAINLESS	212	100	28.50	7.40	18.90	10.5	39.7	208
43600.0003	H5X	STAINLESS	212	100	28.50	7.40	18.90	10.5	39.7	240
43600.0010	H5X	BLACK	212	100	28.50	7.40	18.90	10.5	39.7	208
43600.0026	H5X	STAINLESS	212	100	28.50	7.40	18.90	4.7	17.8	120
43600.0027	H5X	STAINLESS	212	100	28.50	7.40	18.90	10.5	39.7	208
43600.0040	H5X	BLACK	212	100	28.50	7.40	18.90	4.7	17.8	120
43600.0042	H5X	STAINLESS	212	100	28.50	7.40	18.90	18.5	70.0	240
43600.0044	H5X	STAINLESS	212	100	28.50	7.40	18.90	18.5	70.0	208

Constant Temperature *Pourover & Low Volume*

High quality, easy-to-clean stainless steel exterior and tank for a long life

Includes drip tray

HW2

Hooked to water line so fresh, hot water is always available

2gal (7.57L) of hot water in a space-saving machine

OHW

Compact styling to accommodate a variety of spaces

Pourover model. No plumbing needed



OHW



HW2

Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION							TANK SIZE		CAPACITY		ELECTRICAL
Product #	Model	Dimensions			Temperature Setting		gal	L	gal/hr	L/hr	Volts
		Height x Width x Depth			°F	°C					
		(Inches)									
02500.0001	HW2	23.80	7.10	14.30	200	93.3	2	7.6	4.1	15.5	120
02550.0003	OHW	16.90	6.50	10.80	200	93.3	.625	2.4	POUROVER		120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Constant Temperature *Large Volume*

High quality, easy-to-clean stainless steel exterior and tank for a long life

H5E-DV PC

Constant temperature control between 65°F-200°F (18.3°C-96.1°C) ensures consistent water temperature

Dual Voltage (DV) model can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H5X-DV-PC

Dispenses at temperatures up to boiling 212°F (100°C) for food prep and cleaning

Dual Voltage (DV) model can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H10X

Dry-plug prevention for easy installation

Precise temperature (212°F / 100°C) ensures consistent, high quality results



Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION									CAPACITY		ELECTRICAL
									WATER INPUT 60°F / 15.5°C		
Product #	Model	Dimensions Height x Width x Depth (Inches)			Temperature Setting		Tank Size		gal/hr	L/hr	Volts
					°F	°C	gal	L			
39100.0000	H5E-DV PC	28.40	7.00	15.50	200	93.3	5	18.9	5.1	19.3	120
									8.6	32.6	120/208
									11.4	43.2	120/240
39100.0005	H5X-DV PC	28.40	7.00	15.50	212	100	5	18.9	4.7	17.8	120
									7.9	29.9	120/208
									10.5	39.7	120/240
26300.0001	H10X-80-208	34.40	10.20	24.50	212	100	10	37.9	10.5	39.7	208
26300.0000	H10X-80-240	34.40	10.20	24.50	212	100	10	37.9	10.5	39.7	240

A high-quality photograph of a tall, clear glass filled with cold water, ice cubes, and fresh raspberries and blueberries. The glass is set on a rustic wooden surface. In the foreground, more raspberries and blueberries are scattered on the wood, along with a sprig of green herbs. The image is overlaid with several semi-transparent blue geometric shapes (squares and diamonds) on the left side. The text "COLD WATER" is centered in the lower half of the image in a white, sans-serif font.

COLD WATER

BUNN refresh® Tower

Purified, cold water dispenser for still and sparkling water using a patented in-line mistifier

Sleek visual design language worthy of front-of-house settings

One water filtration system included. Purity achieved with water filtration technology certified to reduce cyst, lead, particulates, chloramines, chlorine taste and odor, and 99.99% of common water-borne bacteria.*

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 40°F water

In-line patented water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

Fast flow faucet accommodates large cups or carafes up to 12" tall

At a rate of two 12oz drinks per minute, can dispense 120 drinks before exceeding 41°F

*As tested with E.Coli ATCC (11229) by manufacturer's laboratory.



Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION								ELECTRICAL
Product #	Model	Finish	Temperature Setting		Dimensions* Height x Width x Depth (Inches)			Volts
			°F	°C				
45900.0100	BUNN REFRESH TOWER PULL & HOLD	SATIN CHROME/BLACK	40	4.4	24.75	7.75	14.50	120
45900.0101	BUNN REFRESH TOWER PUSH BUTTON	SATIN CHROME/BLACK	40	4.4	20.10	7.80	14.60	120
Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting								

*Dimensions for tower unit. For tower and undercounter base dimensions please visit bunn.com

BUNN refresh® Counter Top

Purified, cold water dispenser for still and sparkling water using a patented in-line mistifier

One water filtration system included. Purity achieved with water filtration technology certified to reduce cyst, lead, particulates, chloramines, chlorine taste and odor, and 99.99% of common water-borne bacteria.*

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 40°F water

In-line patented water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

The perfect instrument to incorporate infusions and natural ingredients for crafted beverages

Visual design language worthy of front-of-house settings

At a rate of one 12oz drink per minute, can dispense 60 drinks before exceeding 41°F

*As tested with E.Coli ATCC (11229) by manufacturer's laboratory.



BUNN refresh®
Portion Control



BUNN refresh®
Push Button



BUNN® refresh®
Push Button

Prop 65 Warning for California Residents
This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

DESCRIPTION								ELECTRICAL
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			Volts
			°F	°C				
45800.0000	BUNN REFRESH COUNTERTOP PUSH BUTTON	BLACK/STAINLESS	40	4.4	27	10	26.5	120
45800.0001	BUNN REFRESH COUNTERTOP PORTION CONTROL	BLACK/STAINLESS	40	4.4	27	10	26.5	120
45800.0002	BUNN REFRESH COUNTERTOP PUSH BUTTON	WHITE/STAINLESS	40	4.4	27	10	26.5	120
45800.0003	BUNN REFRESH COUNTERTOP PORTION CONTROL	WHITE/STAINLESS	40	4.4	27	10	26.5	120
Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting								

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.





Premium Filtered Water

Expand your beverage menu with profitable, custom-crafted still and carbonated filtered water infusions.

Hot Water on Demand

Hot water is a staple in every type of foodservice operation. From quality beverages to efficient food preparation to reduced labor costs, the value of readily available hot water is invaluable. BUNN

offers a full line of plumbed and pourover

Hot Water Dispensers to meet your on-demand hot water requirements.



CORPORATE HEADQUARTERS

5020 Ash Grove Drive, Springfield, IL USA 62711
(+1) 217-529-6601 • 800-637-8606



www.bunn.com