

A glass pitcher and a glass jar filled with iced tea, garnished with lemons and mint leaves, on a wooden surface. The pitcher is on the right, and the jar is on the left. Both are filled with a golden-brown liquid, ice cubes, lemon slices, and fresh mint leaves. The background is a rustic wooden surface. The image is overlaid with a geometric pattern of blue and white shapes on the left side.

ICED TEA EQUIPMENT



Elements of Commercial Tea Preparation



Water

Because of tea's light flavor compared to other beverages, water quality is crucial. Installation of a filtration unit on the incoming supply is recommended. This will help correct water hardness, remove any chemical taste or odor, and promote longer operational life for the brewing equipment. Brewers have valves, sprayheads and heating elements that are susceptible to clogging, especially in high mineral areas. Use a calibrated thermometer each week to make sure that brewing water in your equipment meets the recommended temperature.



Tea

Finished tea is only as good as the water and the tea variety used. Start with high quality tea and ask suppliers about specific blends and controls used in the supply chain. Tea leaves quickly absorb odors from the air, so store it in airtight containers in a dark, cool place. Because of its natural properties, brewed tea is susceptible to bacterial contamination and growth. Never hold it for more than 12 hours at room temperature and only brew what you reasonably expect to sell in that time.



Equipment

Digital programming in today's brewing equipment offers simple yet precise control over the steeping process. Special funnels designed for tea preparation are available, and the correct dispenser is also important in protecting optimum flavor and potential profit. BUNN offers portable, insulated options for every serving environment.



Cleanliness

Every surface touched by brewed tea becomes susceptible to bacteria growth. Clean and sterilize tea equipment at least once a day. A commercial hot water dispenser is very helpful in the following steps:

Completely dismantle dispensing spigots, hoses, dispenser reservoirs, including removal of O-rings and gaskets. Take special care to sterilize the dispensing spigot according to manufacturer directions.

Wash all parts with detergent or sterilize in 200°F (96.1°C) hot water, removing any deposits with a brush. Rinse with warm water. Replace worn gaskets, O-rings, or other damaged parts before reassembling.

Infusion Series® Standard Edition Iced Tea

Achieve a variety of flavor profiles and batch options in a single unit

Three recipe buttons and full/half options for maximum flexibility; brew counter tracks number of batches

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.

Single button graphic overlay to customize user interface

Quickbrew (Q) funnel tip for easy conversion

ITB-DD DUAL DILUTION

Narrow footprint, designed to brew into two BUNN® TDO-N 3.5gal dispensers

Rotating brew basket, base adapter, color-coded decals, and dedicated dilution nozzles included

ITB & ITB-DD SWEETENER

Easily adjust sweetener volume with the Sweet Meter

Separate sweetener inlet - use existing CO₂ systems or external third party pump for sweetener delivery

ITB-LP LOW PROFILE

Brew directly into TDO-3.5 LP dispenser with brew-thru lid

Compact, low-profile styling for variety of spaces



Servers sold separately



Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

| DESCRIPTION | | | | | | PAPER FILTER | CAPACITY | CAPACITY W/Q FUNNEL TIP | ELECTRICAL |
|--|------------------------|-----------|--|-------|-------|--------------|------------------------------|------------------------------|------------|
| Product # | Model | Sweetener | Dimensions Height x Width x Depth (Inches) | | | BUNN # | 8oz cups/hr 236mL cups/hr | 8oz cups/hr 236mL cups/hr | Volts |
| 52000.0000 | ITB | NO | 35.00 | 11.60 | 21.80 | 20100.0000 | 336 | 523 | 120 |
| Compatible tea dispensers - TDO-5, TDO-4, TD4T, TDS-3, TDS-3.5, TDO-N 3.5, TDO-N 4, TD3T-N | | | | | | | | | |
| 52000.0300 | ITB DD w/ Sweetener | YES | 35.00 | 12.20 | 21.80 | 20100.0000 | 336 | 523 | 120 |
| 52000.0301 | ITB DDIL | NO | 35.00 | 12.20 | 21.80 | 20100.0000 | 336 | 523 | 120 |
| Compatible tea dispensers - TDO-N 3.5, TDO-N 4, TD3T-N | | | | | | | | | |
| 52000.0101 | ITB-LP | NO | 29.50 | 11.60 | 21.80 | 20100.0000 | 336 | 523 | 120 |
| Compatible tea dispensers - TDO-3.5 LP | | | | | | | | | |

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Automatic Iced Tea Single

Fresh iced tea brewing solution with simple switch operation

TB3, TB3Q

Choose between 25.75" or 29" trunk heights (see table for compatible dispensers)

Dispenser sold separately (except TB3Q w/TD4T)

Quickbrew (Q) models include special funnel tip for shorter brewing cycle

TB3Q-LP LOW PROFILE

Brew directly into TDO-3.5 LP dispenser (included) with brew-thru lid

Quickbrew (Q) models include special funnel tip for shorter brewing cycle

Compact, low profile styling to accommodate a variety of space



Servers sold separately

Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

| DESCRIPTION | | | | | | | | PAPER FILTER | CAPACITY | ELECTRICAL |
|--|---------|-----------|-------------|--------------------|--|-------|-------|--------------|------------------------------|------------|
| Product # | Model | Quickbrew | Ready Light | Dispenser Included | Dimensions Height x Width x Depth (Inches) | | | BUNN # | 8oz cups/hr 236mL cups/hr | Volts |
| 29" TRUNK HEIGHT | | | | | | | | | | |
| 36700.0009 | TB3 | NO | NO | NO | 34.00 | 11.60 | 22.00 | 20100.0000 | 303 | 120 |
| 36700.0013 | TB3Q | YES | NO | NO | 34.00 | 11.60 | 22.00 | 20100.0000 | 523 | 120 |
| 36700.0041 | TB3Q | YES | NO | YES (TD4T) | 34.00 | 11.60 | 22.00 | 20100.0000 | 523 | 120 |
| 36700.0055 | TB3 | NO | YES | NO | 34.00 | 11.60 | 22.00 | 20100.0000 | 303 | 120 |
| Compatible tea dispensers - TDO-5, TDO-4, TD4T (Included with TB3QT), TDS-3, TDS-3.5, TDO-N-3.5, TD3T-N, TDO-N-4 | | | | | | | | | | |
| 25.75" TRUNK HEIGHT | | | | | | | | | | |
| 36700.0030 | TB3 | NO | NO | NO | 31.00 | 11.60 | 22.00 | 20100.0000 | 303 | 120 |
| 36700.0059 | TB3Q | YES | NO | NO | 31.00 | 11.60 | 22.00 | 20100.0000 | 523 | 120 |
| Compatible tea dispensers - TD4, TDS-3, TDO-4 | | | | | | | | | | |
| LOW PROFILE | | | | | | | | | | |
| 36700.0100 | TB3Q-LP | YES | NO | YES (TDO3.5 LP) | 28.75 | 11.57 | 21.87 | 20100.0000 | 523 | 120 |
| Compatible tea dispensers - TDO-3.5 LP (Included) | | | | | | | | | | |

Automatic Iced Tea Twin Narrow

Fresh iced tea brewing solution with simple switch operation

Specifically designed to accommodate and brew into two BUNN® Narrow Tea Dispensers (can also brew directly into standard tea dispensers)

Includes rotating brew basket, base platform adapter, dedicated dilution nozzles and brew selection switch

Quickbrew (Q) model includes special funnel tip for shorter brewing cycles



 Servers sold separately

Prop 65 Warning for California Residents

This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.

TB6

| DESCRIPTION | | | | | | PAPER FILTER | CAPACITY | ELECTRICAL |
|-------------|-------|-----------|--|-------|-------|--------------|------------------------------|------------|
| Product # | Model | Quickbrew | Dimensions Height x Width x Depth (Inches) | | | BUNN # | 8oz cups/hr 236mL cups/hr | Volts |
| 36700.0300 | TB6 | NO | 34.00 | 12.20 | 22.60 | 20100.0000 | 303 | 120 |
| 36700.0301 | TB6Q | YES | 34.00 | 12.20 | 22.60 | 20100.0000 | 523 | 120 |

Compatible tea dispensers - TDO-N-3.5, TDO-N-4, TD4T, TDS-3, TDS-3.5

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.





CORPORATE HEADQUARTERS

5020 Ash Grove Drive, Springfield, IL USA 62711
(+1) 217-529-6601 • 800-637-8606



www.bunn.com