



HOT DISPENSED BEVERAGE EQUIPMENT



iMIX® 3

Sleek powdered beverage dispenser delivers hot drinks with exceptional reliability and taste - all from an operator-friendly design

Three 8lb hopsers

LED backlit door graphics

Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6g powder per second)

Left or top-hinged door option

Dispense 36 12oz cups in 14 minutes before dropping 10°F from first cup serving temperature

Display allows adjustments and service operational testing from front of machine, communicates machine status, and technical support contact information, and promotional messages

iMIX-3S+

Set as push-and-hold or single size portion control

California residents see
Prop 65 Warning on page 1



iMIX-3 (Top Hinge)



iMIX-3S+



iMIX-3

DESCRIPTION							ELECTRICAL
Product #	Model	Display	Top Hinge Door	Dimensions Height x Width x Depth (Inches)			Volts
36900.0000	iMIX-3	CAPPUCCINO	NO	32.80	12.60	24.10	120
36900.0001	iMIX-3 (SST PANELS)	CAPPUCCINO	NO	32.80	12.60	24.10	120
36900.0050	iMIX-3	CAPPUCCINO	YES	32.80	12.60	24.10	120
38600.0001	iMIX-3S+	CAPPUCCINO	NO	32.80	12.60	24.10	120
38600.0050	iMIX-3S+	CAPPUCCINO	YES	32.80	12.60	24.10	120



iMIX® 5

Sleek, powdered-beverage dispenser delivers hot drinks with exceptional reliability and taste - all from an operator-friendly design

- Five 8lb hopsers
- LED backlit door graphics
- Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6g powder per second)
- Left or top-hinged door option
- Dispense 36 12oz cups in 14 minutes before dropping 10°F from first cup serving temperature
- Display allows adjustments and service operational testing from front of machine, communicates machine status, and technical support contact information, and promotional messages

iMIX-5S+

Set as push-and-hold or single size portion control

California residents see
Prop 65 Warning on page 1



iMIX-5S+



iMIX-5

DESCRIPTION							ELECTRICAL
Product #	Model	Hot Water Dispense	Top Hinge Door	Dimensions Height x Width x Depth (Inches)			Volts
37000.0000	iMIX-5	NO	NO	32.80	19.30	24.00	120
37000.0020	iMIX-5	NO	YES	32.80	19.30	24.00	120
37000.0022	iMIX-5	YES	YES	32.80	19.30	24.00	120
38100.0003	iMIX-5S+	NO	NO	32.80	19.30	24.00	120
38100.0050	iMIX-5S+	NO	YES	32.80	19.30	24.00	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Fresh Mix

Variable-speed motor enables control of product consistency in mixing chamber

FMD-1: One 8lb hopper

FMD-2: Two 4lb hoppers

FMD-3: Three 4lb hoppers

FMD-5: Five 4lb hoppers

Variable speed motors allow control of product consistency in mixing chamber
(.75 to 6.6g powder per second)

Lighted graphics for merchandising

Fast fill – perfect for quick service restaurants

Each mixing chamber has independent powder to water ratio

California residents see
Prop 65 Warning on page 1



FMD-3



FMD-5



FMD-1

DESCRIPTION							ELECTRICAL
Product #	Model	Display	Number of Hoppers	Dimensions Height x Width x Depth (Inches)			Volts
SET00.0196	FMD-1	MUG DISPLAY	ONE	29.50	8.20	21.00	120
SET00.0203	FMD-1	HOT CHOCOLATE DISPLAY	ONE	29.50	8.20	21.00	120
SET00.0200	FMD-2 Black	MUG DISPLAY	TWO	29.50	8.20	21.00	120
SET00.0207	FMD-2 Stainless	MUG DISPLAY	TWO	29.50	8.20	21.00	120
SET00.0197	FMD-3 Black	CAPPUCCINO DISPLAY	THREE	29.80	11.70	23.30	120
SET00.0198	FMD-3 Stainless	CAPPUCCINO DISPLAY	THREE	29.80	11.70	23.30	120
34900.0000	FMD-5	CAPPUCCINO DISPLAY	FIVE	29.30	18.2-	21.20	120

