

A close-up photograph of a Bunn coffee pot pouring coffee into a cup. The image is overlaid with several semi-transparent geometric shapes in shades of blue and white. The Bunn logo is visible on the side of the pot.

SERVING & HOLDING EQUIPMENT



ThermoFresh® Digital Gauge Servers

Holds temperature for hours without traditional warming plates

TF SERVER

Digital timer begins to count up in one minute increments to specifically display how long the brewed beverage has been stored; requires four AAA batteries; display shows low battery symbol

Brew-thru lid design also features a pour spout for easy emptying and cleaning

Open face faucet guard protects the faucet from damage while providing a clear view for dispensing

Ideal for use with Single or Dual TF DBC® and Infusion Series® Brewers

TF SERVER WITHOUT STAND

Ideal with Infusion Series® Coffee Brewer (ICB)

TF SERVER STAND

Use for easy dispensing; 7.1 inch cup clearance

Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels

California residents see
Prop 65 Warning on page 1



3.8L TF Server
without Stand



TF Server Stand



3.8L TF Server
(Stand included)

Product #	Model	Dimensions			Holding Capacity		Includes Stand	Finish	Compatible Brewers
		Height	Width	Depth	Gal	L			
		(Inches)							
42700.0200	TF SERVER DSG3	20.70	9.30	13.00	1.0g	3.8L	YES	STAINLESS	Single TF DBC, Dual TF DBC, ICB Tall, ICB Twin Tall, ITCB-DV, ITCB-DV HV, ITCB Twin HV
42750.0200	TF SERVER DSG3	22.70	9.30	13.00	1.5g	5.7L	YES	STAINLESS	
42700.0250	TF SERVER DSG3	12.60	9.10	11.90	1.0g	3.8L	NO	STAINLESS	
42750.0250	TF SERVER DSG3	14.70	9.10	11.90	1.5g	5.7L	NO	STAINLESS	ICB-DV ICB Twin
54473.1000	TF SERVER STAND	8.77	9.24	12.99	N/A	N/A	N/A	BLACK	N/A

ThermoFresh® Mechanical Gauge Servers

Holds temperature for hours without traditional warming plates

TF SERVER

- Glass sight gauge on front of server allows for visible indication of level capacity
- Brew-thru lid design also features a pour spout for easy emptying and cleaning
- Open face faucet guard protects the faucet from damage while providing a clear view for dispensing
- Ideal for use with Single or Dual TF DBC® Brewers

TF SERVER STAND

- Use for easy dispensing; 7.1 inch cup clearance
- Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels

TITAN TF SERVER

- 3gal or 1.5gal capacity
- Insulated and portable
- Large cup clearance for a variety of dispensing options

California residents see
Prop 65 Warning on page 1



Titan TF Server
(3 gal)



Titan TF Server
(1.5 gal)



3.8L TF Server
without Stand



TF Server Stand

5.7L TF Server
(Stand included)

Product #	Model	Dimensions			Holding Capacity		Includes Stand	Finish	Compatible Brewers
		Height	Width	Depth	Gal	L			
44000.0200	TF SERVER	20.70	9.30	13.00	1.0g	3.8L	YES	STAINLESS	Single TF DBC, Dual TF DBC, ICB Tall, ICB Twin Tall, ITCB-DV, ITCB-DV HV, ITCB Twin HV
44050.0200	TF SERVER	22.74	9.24	12.99	1.5g	5.7L	YES	STAINLESS	
46300.0000	TITAN TF SERVER	22.90	11.70	15.30	1.5g	5.7L	NO	STAINLESS	
39400.0001	TITAN TF SERVER	23.70	13.80	17.30	3.0g	11.4L	NO	STAINLESS	Titan Single, Titan Dual
44000.0250	TF SERVER	12.60	9.10	11.80	1.0g	3.8L	NO	STAINLESS	ICB-DV ICB Twin
44050.0250	TF SERVER	14.68	9.07	11.87	1.0g	3.8L	NO	STAINLESS	
54473.1000	TF SERVER STAND	8.77	9.25	12.99	N/A	N/A	N/A	BLACK	N/A

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Coffee Decanters and Warmers

EASY POUR®

BUNN® exclusive design; high quality stainless steel base with drip proof, fast-pour lip

Clear, impact-resistant material complies with FDA regulations for food contact

Glass decanters

Reliable, shatter-resistant, and perfectly balanced with laboratory-grade, stress-free glass

RFID decanters

Replaceable RFID collar tracks coffee freshness with compatible brewers

Warmers

Ideal solution for remote serving; separate "on/off" switch

California residents see
Prop 65 Warning on page 1



Glass



Easy Pour®



Stainless Steel



Glass with RFID



WX2 Side by Side

DECANTERS						COMPATIBLE EQUIPMENT
Product #	Model	Capacity OZ	L	Handle Color	Quantity Per Case	Brewers
06026.0000	STAINLESS	64oz	1.9L	BLACK	1	12 Cup Decanter Brewers: VP17 VPR VPS AXIOM CW CWT CWTF CRTF RL VLPF
06100.0101	EASY POUR	64oz	1.9L	BLACK	1	
06100.0102	EASY POUR	64oz	1.9L	BLACK	2	
06100.0103	EASY POUR	64oz	1.9L	BLACK	3	
06100.0106	EASY POUR	64oz	1.9L	BLACK	6	
06100.0112	EASY POUR	64oz	1.9L	BLACK	12	
06100.0124	EASY POUR	64oz	1.9L	BLACK	24	
06101.0101	EASY POUR	64oz	1.9L	ORANGE	1	
06101.0102	EASY POUR	64oz	1.9L	ORANGE	2	
06101.0103	EASY POUR	64oz	1.9L	ORANGE	3	
06101.0124	EASY POUR	64oz	1.9L	ORANGE	24	
42400.0024	GLASS	64oz	1.9L	BLACK	24	
42400.0101	GLASS	64oz	1.9L	BLACK	1	
42400.0103	GLASS	64oz	1.9L	BLACK	3	
42401.0024	GLASS	64oz	1.9L	ORANGE	24	
42401.0101	GLASS	64oz	1.9L	ORANGE	1	
42401.0103	GLASS	64oz	1.9L	ORANGE	3	
42400.0203	GLASS	64oz	1.9L	BLACK	3	AXIOM RFID
42401.0203	GLASS	64oz	1.9L	ORANGE	3	AXIOM RFID
WARMERS						
Product #	Model	Finish		Number of Warmers		Volts
06310.0004	WX2 SIDE BY SIDE	STAINLESS		2		120
06450.0004	WX1	STAINLESS		1		120
11402.0001	WL2 STEP UP	STAINLESS		2		120



Thermal Carafes, Pitchers and Airpots

Thermal Carafe

Highly durable stainless steel interior and exterior

Thermal Pitcher

Stainless steel lining ensures hot coffee for hours

Push Button Airpot

Brew-thru pump assembly - no need to remove for brewing

Lever-Action Airpot

Brew-thru lid with lever-action for easy use



Vacuum Pitcher



Lever-Action Airpot



Push-Button Airpot



Seamless Thermal Carafe



Thermal Carafe

California residents see
Prop 65 Warning on page 1

CARAFES							COMPATIBLE EQUIPMENT
Product #	Model	Capacity OZ	L	Liner	Lid Color	Quantity per Case	Brewers
36029.0001	DELUXE THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	BLACK	ONE	VPR-TC CW15-TC AXIOM-DV-TC SmartWAVE CWTF-TC
36029.0000	DELUXE THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	BLACK	TWELVE	
36252.0001	DELUXE THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	ORANGE	ONE	
36252.0000	DELUXE THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	ORANGE	TWELVE	
51746.0001	SEAMLESS THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	BLACK	ONE	
51746.0101	SEAMLESS THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	BLACK	TWELVE	
51746.0002	RFID SEEMLESS THERMAL CARAFE	64OZ	1.9L	STAINLESS STEEL	RED	ONE	
51746.0003	SEAMLESS THERMAL CARAFE	64oz	1.9L	STAINLESS STEEL	BLACK/ORANGE	ONE	
PITCHERS							
Product #	Model	Capacity OZ	L	Liner		Quantity per Case	Brewers
39430.0000	VACUUM	64oz	1.9L	STAINLESS STEEL		ONE	SmartWAVE
39430.0100	VACUUM	64oz	1.9L	STAINLESS STEEL		SIX	SmartWAVE
AIRPOTS							COMPATIBLE EQUIPMENT
Product #	Model	Capacity OZ	L	Liner		Quantity per Case	Brewers
28696.0002	PUSH-BUTTON	74oz	2.2L	GLASS		ONE	VPR-APS CW15-APS ICB-DV AXIOM-DV-APS AXIOM Twin APS SmartWAVE CWTF-APS ITCB-DV (flip tray)
28696.0006	PUSH-BUTTON	74oz	2.2L	GLASS		SIX	
13041.0001	PUSH-BUTTON	84oz	2.5L	GLASS		ONE	
13041.0101	PUSH-BUTTON	64oz	2.5L	GLASS		SIX	
32700.0000	LEVER-ACTION	74oz	2.2L	GLASS		SIX	
32125.0000	LEVER-ACTION	84oz	2.5L	STAINLESS STEEL		ONE	
32125.0100	LEVER-ACTION	84oz	2.5L	STAINLESS STEEL		SIX	
32130.0000	LEVER-ACTION	102oz	3.0L	STAINLESS STEEL		ONE	
32130.0100	LEVER-ACTION	102oz	3.0L	STAINLESS STEEL		SIX	
36725.0000	LEVER-ACTION	128oz	3.8L	STAINLESS STEEL		ONE	
36725.0100	LEVER-ACTION	128oz	3.8L	STAINLESS STEEL		SIX	

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Soft Heat® Server System

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

SH Server

1.5Gal capacity; choose from five optional holding time settings

Safety-Fresh® brew-thru lid with vapor seal and spill prevention

Soft grip handle for secure portability

SH Docking Station

Remote one and two server docking stations with 4 inch legs

Instant power contact with servers

Add additional remote stations to increase volume

California residents see
Prop 65 Warning on page 1



2SH Docking Station



1 SH Server and Docking Station

DESCRIPTION						ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (Inches)			Volts
27825.0200	INFUSION SERIES® 1SH DOCKING STAND	STAINLESS	9.30	10.20	11.80	120
27825.0201	INFUSION SERIES® 1SH DOCKING STAND W/ COMM *	STAINLESS	9.30	10.20	11.80	120
27875.0200	INFUSION SERIES® 2SH DOCKING STAND	STAINLESS	9.30	20.20	11.80	120
27875.0201	INFUSION SERIES® 2SH DOCKING STAND W/ COMM*	STAINLESS	9.30	20.20	11.80	120
27850.0200	INFUSION SERIES® 5.7L SH SERVER	BLACK/STAINLESS	14.50	9.10	13.30	24

[*For More Information on stands with wi-fi communication visit bunn.com](#)

Universal Airpot Racks

Versatile merchandising system for airpots

Displays can be combined or taken apart easily for greater flexibility

Sturdy, carbon-steel wire construction with vinyl coating resists corrosion, easy to clean

Configurations available for two to six airpots

California residents see
Prop 65 Warning on page 1



UNIV-4 APR



UNIV-3 APR



UNIV-2 APR

DESCRIPTION

Product #	Model	Dimensions Height x Width x Depth (Inches)			Capacity
35728.0000	UNIV-2 APR (1 Upper, 1 Lower)	14.10	7.50	24.10	Two Airpots
35728.0001	UNIV-2 APR (2 Lower)	6.90	14.90	11.20	Two Airpots
35728.0002	UNIV-3 APR (3 Lower)	6.90	22.90	28.45	Three Airpots
35728.0003	UNIV-4 APR (2 Upper, 2 Lower)	14.00	14.90	24.90	Four Airpots
35728.0004	UNIV-5 APR (3 Upper, 2 Lower)	14.00	22.90	24.90	Five Airpots
35728.0005	UNIV-6 APR (3 Upper, 3 Lower)	14.00	22.90	24.90	Six Airpots

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



GPR Servers and Remote Warmers

Convenient servers and warming stands allow for easy set-up and maintenance of remote serving stations

PORTABLE SERVER

- 1.5gal capacity
- Top handle allows for easy transport to remote service
- Safety-Fresh® brew-thru lid with vapor seal and spill prevention

WARMER

- Adjustable black plastic legs

California residents see
Prop 65 Warning on page 1



RWS1 Warmer



1.5 GPR-FF

DESCRIPTION									
Product #	Model	Dimensions Height x Width x Depth (Inches)			Capacity gal L		Finish	Volts	Compatible Equipment
12203.0010	RWS1 WARMER Black Legs	7.50	8.25	9.30	One GPR Server		STAINLESS	120	1.5GPR
20950.0004	1.5 GPR-FF	9.10	6.70	12.73	1.5	5.7	STAINLESS	N/A	Single GPR DBC, Dual GPR DBC, AXIOM Single, Single and Dual

Iced Tea and Iced Coffee Dispensers

Solid stainless construction stands up to demands of foodservice environments

Sump dispense valves assure complete dispensing of beverage

Variety of shapes and sizes for every counter configuration

California residents see
Prop 65 Warning on page 1



Square



Oval



Round



Narrow



TDO-N Low Profile Dispenser (Top)
TDO-N Narrow Dispenser (Lower)
w/ Dispense Rack Single LP

Please see specification table on following page

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

NARROW									
Product #	Model	Dimensions			Capacity		Handles	Additional Feature	Compatible Equipment
		Height x Width x Depth (Inches)	gal	L					
39600.0001	TDO-N-3.5	21.8	6.2	13.6	3.5	13.2	FRONT/BACK	STANDARD DISPENSE FAUCET	TALL MODELS w/29" TRUNK: TB3, TB6 ITB, ITB DD ITCB, ITCB HV ITCB TWIN HV
39600.0031	TDO-N-3.5	21.8	6.2	13.6	3.5	13.2	FRONT/BACK	LIFT DISPENSE FAUCET	
39600.0047	TDO-N-3.5	21.8	6.2	13.6	3.5	13.2	FRONT/BACK	SOLID LID, PINCH TUBE FAUCET	
39600.0002	TDO-N-4.0	21.0	6.0	23.6	4	15	FRONT/BACK	STANDARD DISPENSE FAUCET	
43900.0001	TD3T-N	22.7	6.2	15.1	3.5	13.2	FRONT/BACK	LIFT HANDLE, BREW-THRU LID	
43900.0002	TD3T-N	22.7	6.2	15.1	3.5	13.2	FRONT/BACK	LIFT HANDLE, SOLID LID	
SQUARE									
03250.0003	TD4	17.1	9.1	15.7	4	15.1	SIDE	SOLID LID	SHORT MODELS w/ 25.75" TRUNK: TB3 ITB ITCB
03250.0006	TD4	17.1	9.1	15.7	4	15.1	SIDE	BREW-THRU LID	
03250.0004	TD4T	22.0	9.1	15.7	4	15.1	SIDE	SOLID LID, TALL	TALL MODELS w/ 29" TRUNK: ITB ITCB ITCB HV
03250.0005	TD4T	22.0	9.1	15.7	4	15.1	SIDE	BREW-THRU LID, TALL	
03250.0018	TD4T	22.0	9.1	15.7	4	15.1	SIDE	BREW-THRU LID, TALL, NO DECAL	
CYLINDER - ROUND									
33000.0000	TDS-3	19.0	9.8	12.8	3	11.4	SIDE	STAINLESS LID	TB3 ITB
33000.0023	TDS-3.5	20.4	9.8	12.8	3.5	13.2	SIDE	STAINLESS LID	ITCB ITCBHV
33000.0001	TDS-5	25.6	9.8	14.8	5	18.9	SIDE	STAINLESS LID	TU5
CYLINDER - OVAL									
34100.0000	TDO-4	19.0	10.7	13.7	4	15	SIDE	SOLID, PLASTIC LID	TB3 ITB ICB ITCB HV
34100.0002	TDO-4	19.0	10.7	13.7	4	15	SIDE	BREW-THRU PLASTIC LID	
34100.0001	TDO-5	22.0	10.7	13.7	5	18.9	SIDE	SOLID, PLASTIC LID	
34100.0003	TDO-5	22.0	10.7	13.7	5	18.9	SIDE	BREW-THRU PLASTIC LID	
LOW PROFILE									
39600.0066	TDO-N-2.0 LP	10.3	6.2	13.6	2	7.5	FRONT/BACK	STANDARD DISPENSE FAUCET	SHORT MODELS w/ 25.75" TRUNK: TB3 ITB ITCB
39600.0065	TDO-N-3.5 LP	15.2	6.2	13.6	3.5	13.2	FRONT/BACK	STANDARD DISPENSE FAUCET	
37100.0000	TDO-3.5 LP	10.0	9.8	16.1	3.5	13.2	SIDE	BREW-THRU PLASTIC LID	TB3 LP, ITB LP
ACCESSORIES									
49634.0000	DISPENSE RACK SINGLE LP	24.5	6.5	17.8	N/A	N/A	SIDE	N/A	TDO-N-2.0 LP TDO-N-3.5 LP
50845.0000	BOOSTER WIRE FORM	11.0	8.9	13.7	N/A	N/A	SIDE	N/A	TDO-N-2.0 LP TDO-N-3.5 LP
37675.0001	REMOTE SERVER STAND	9.1	11.6	14.0	N/A	N/A	TOP	N/A	TDO-3.5 LP
50534.1000	SLIDE LID ASSEMBLY	1.5	6.3	15.0	N/A	N/A	N/A	N/A	TDO-N-2.0 LP TDO-N-3.5 LP

Brewed coffee and tea should be enjoyed while flavor and aroma are at their peak.

BUNN® offers a range of holding and serving equipment designed to keep your beverage at its best.

Keep your coffee at its best.

Ideal holding temperature: 175°F to 185°F

Most volatile aromatics in coffee have boiling points well below that of water and continue to evaporate from the surface until pressure in the serving container reaches equilibrium. A closed container can slow the process of evaporation.

Ideal serving temperature: 155°F to 175°F

Volatile aromatics in coffee are not perceived when coffee is served at lower temperatures.

Ideal holding time: 20 minutes in an open top decanter/60 minutes in a closed container

Holding coffee longer will result in loss of the smooth, sweet and complex flavors and instead produce a scorched or bitter taste.

Iced tea at its peak

Because of its natural properties, brewed tea is susceptible to bacterial contamination and growth. Never hold it for more than 12 hours at room temperature and only brew what you reasonably expect to sell in that time.



CORPORATE HEADQUARTERS

5020 Ash Grove Drive, Springfield, IL USA 62711

(+1) 217-529-6601 • 800-637-8606



www.bunn.com