

ASIA PACIFIC EQUIPMENT CATALOG



TABLE OF CONTENTS

BREWED BEVERAGES

	COFFEE	5
	Infusion Series® Brewers	5
	Soft Heat Brewers	7
	TF Brewers	9
	Thermal Brewers	11
	Decanter Brewers Pourover Brewers	15 17
	High Volume Brewers	20
	GRINDERS	23
	BEAN-TO-CUP	30
	COFFEE & TEA COMBOS	33
DISPENSED BEVERAGES		
	COLD COFFEE	36
	HOT CHOCOLATE/CAPPUCCINO	40
	HOT WATER	42
	FROZEN GRANITA/SLUSHY	46
ACCESSORIES/EXTRAS		
	SERVING & HOLDING	49
	PAPER FILTERS	58
	ACCESSORIES	60
	CLEAN CONTACT SOLUTIONS	64
	VirtualTOUCH™	65

DID YOU KNOW THAT WE HAVE LOCATIONS AROUND THE WORLD TO SERVE YOU?



CANADA - AURORA, ONTARIO • MEXICO - MEXICO CITY • BRAZIL - SÃO PAULO UNITED KINGDOM - BIRMINGHAM • CHINA - SHANGHAI • CHINA - SHENZHEN

AGENCY SYMBOLS



NSF, NSF International (CE Listed





EHI EurAsian Conformity Mark



KOREA South Korea



China Compulsory
Certification



Electrical Testing Labs Sanitation



Electrical Testing Labs Safety



ELECTRICAL PLUGS











NEMA-5-15P



Infusion Series® Platinum Edition®

The Infusion Series Platinum Edition line of brewing equipment is equipped with an intuitive touch screen, providing an enhanced user experience when operating and programming the brewers

ICB and ICB Twin

Intuitive 10.9cm touchscreen with user interface provides an enhanced experience when operating and programming the brewers

The Infusion Series® Platinum Edition relies on the powerful duo of the Peak Extraction Sprayhead and SmartWAVE® technology to further enhance the uniformity of extraction and resistance to limescale buildup.

USB port for easy programming

Digital readout displays in English, Spanish, or French ---for easier programming and control

Electronic funnel lock prevents removal of each brew funnel until drip- through is complete

ICBA PE is compatible with new TF 3.8-Liter Baseless ThermoFresh® Servers, all previous generations of TF 3.8-Liter Baseless TF Servers, and Airpots

ICB TF 54200.0500 is compatible with new TF 1.5-gallon ThermoFresh® Servers (with Base), all previous generations of TF 1.5-gallon TF Servers (with Base), Titan® 1.5-gallon servers, and Airpots

ICB Twin TF 54300.0500 is compatible with new TF 1.5-gallon ThermoFresh® Servers (with Base), all previous generations of TF 1.5-gallon TF Servers (with Base), Titan® 1.5-gallon servers, and Airpots











ICB PE

ICB TF 1.5 PE

ICB Twin TF

		DESCR	IPTION				CAPACITY			ELECTRICAL	L			AGENCY
Product #	Model	Finish	Funnel Type	Height	imension Width entimete	x Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
53300.0500	ICBA PE	STAINLESS	BLACK/SMART	68.10	25.40	56.13	141	220-240	11.0-12.0	2400-2900	50-60	1	EURO	C€
53300.0501	ICBA PE	STAINLESS	STAINLESS/ SMART	68.10	25.40	56.13	141	220-240	11.0-12.0	2400-2900	50-60	1	UK	(E
54200.0500	ICB TWIN TF 1.5 PE, 200V SST	STAINLESS	STAINLESS/ SMART	86.4	57.4	59.2	82 136 181	200	27.8	5550	50-/60	1		
54300.0500	ICB TF 1.5 PE, 200V SST	STAINLESS	STAINLESS/ SMART	86.4	30.7	60.5	150	200	16.2	3240	50-60	1		
54300.0501	ICB TF 1.0 PE, 200V SST	STAINLESS	STAINLESS/ SMART	86.4	30.7	60.5	150	200	16.2	3240	50-60	1		

SOLD SEPARATELY



20138.1000



Inlet Hose Assembly 32865.1002





Legs 00511.0000



Infusion Series® Standard Edition

The Infusion Series coffee and tea equipment platform provides Best Result In The Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ICBA & ICBB

Sleek modernized design language on the brewer and servers

The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup

Three brew buttons and two batch sizes allow for multiple brewing profiles

Easy Pulse programing automatically adjusts contact time for optimal flavor profile

Compatible with BrewWISE® intelligence





ICB

												ICD		
		DESC	RIPTION				CAPACITY			ELECTRICA	AL			AGENCY
Product #	Model	Finish	Funnel Type	Height 2	imensio x Width entimete	x Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
53100.0501	ICBA	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	220-240	11-12	2400-2900	50-60	1	UK	C€
53100.0502	ICBA	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	220-240	11-12	2400-2900	50-60	1	EURO	C€
53100.0504	ICBB	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	200	18	3600	50-60	1		
53100.0505	ICBA	STAINLESS	BLACK/SMART	63.10	25.40	55.90	141	220-240	11-12	2400-2900	50-60	1	KOREA	[]
53100.0506	ICBA	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	220-240	11-12	2400-2900	50-60	1	N/A	
53100.0507	ICBA	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	220-240	13.2-14.1	2900-3400	50-60	1	CHINA	
53100.0510	ICBB 200V	STAINLESS	BLACK/SMART	68.10	25.40	55.90	141	200	25.4	8799	50-60	3	N/A	



Single/Dual Filter Pack 20138.1000



Inlet Hose Assembly 32865,1002



Server



Legs 00511 0000



Infusion Series® Soft Heat® Edition

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

ICB SH AND TWIN SH

Sleek modernized design language on the brewer and servers

Three brew buttons and three batch sizes allow for multiple brewing profiles

Easy Pulse programming automatically adjusts contact time for optimal flavor profile

Wireless Server monitoring on some models allows for remote tracking of coffee freshness on mobile devices

New Infusion Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy efficient and now offer programmable recipe/batch based holding times and temperatures, alerting staff when freshness has expired or server is empty

Compatible with new TF 5.7L ThermoFresh® Servers (without Base), and all previous generations of TF 5.7L TF Servers (without Base)

The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup



Soft Heat® Stainless











		DESCRI	PTION				CAPACITY			ELECTRIC	CAL			AGENCY
Product #	Model	Finish	Funnel Type	Height >	imension Width >	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
51100.0500	ICBA SH	STAINLESS	BLACK/SMART	83.3	30.0	59.4	163	220-240	13.2-14.1	2900- 3400	50-60	1	EURO	C€
51100.0502	ICBA SH	STAINLESS	BLACK/SMART	88.3	30.0	59.4	163	220-240	13.2-14.1	2900- 3400	50-60	1	EURO	C€
52100.0500	ICBB SH PE, 200V W/WRLESS	STAINLESS	STAINLESS	83.3	30.0	58.9	259	200	16.2	3240	50-60	1		
53600.0500	ICB TWIN SH PE, 200V SST W/WRLESS	STAINLESS	STAINLESS	83.3	55.6	58.4	259	200	27.7	5560	50-60	1		





Inlet Hose Assembly 32865.1002



Soft Heat® Single®

BUNN-exclusive Soft Heat® technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

Brews 1.9, 3.8 or 5.7L batches

Brews up to 43.2L per hour with three variable batch sizes

Instant power contact with docking station; server can be set to 79.4° – 87.8°C

Metric volume and Celsius temperature settings

BrewWISE® intelligence means compatible grinders and a Smart Funnel® can be programmed one time to manage repeated brewing cycles from start to finish





Single SH DBC

	DESCRIPTION					CAPACITY			ELECTRICA	AL			AGENCY
Product #	Model	Funnel Type	Height	imension x Width a entimete	Depth	236mL cups/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
33600.0006	SINGLE SH DBC	SMART	90.93	23.62	62.7	214	230	19	4400	50-60	1	NO	NSE CE
33600.0012	SINGLE SH DBC	STAINLESS	90.93	23.62	58.67	157	220-240	14.5-15.7	3180-3780	50-60	1	KOREA	KSF)

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Single/Dual Filter Pack 20138.1000

SOLD SEPARATELY



Inlet Hose Assembly 32865.1002



One Position Drip Tray 26830.0000

ThermoFresh® Single®

 $\mathsf{TF}\ \mathsf{brewers}\ \mathsf{use}\ \mathsf{Digital}\ \mathsf{Brewer}\ \mathsf{Control}^{\scriptscriptstyle\mathsf{IM}}\ \mathsf{with}\ \mathsf{insulated}\ \mathsf{ThermoFresh}\ \mathsf{servers}\ \mathsf{that}\ \mathsf{keep}\ \mathsf{bevarages}\ \mathsf{hot}\ \mathsf{without}$ requiring the energy consumption of traditional warming plates

Three variable batch sizes

SplashGard® funnel and funnel locks help improve safety

BrewWISE® intelligence means compatible grinders and a Smart Funnel® can be programmed one time to manage repeated brewing cycles from start to finish

Stores individual coffee recipes so operator can easily brew many varieties





Single TF DBC Stainless

		DESCRIPTION	ON				CAPACITY			ELECTRICA	AL			AGENCY
Product #	Model	Finish	Funnel Type	Height 2	imensior k Width : entimete	x Depth	236mL cups/hr**	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
34800.0012	SINGLE TF DBC	STAINLESS	SMART	90.68	30.73	57.7	140-182	220-240	14.5-15.7	3180-3780	50-60	1	EURO	(€ 💩
34800.0036	SINGLE TF DBC	STAINLESS	SMART	90.68	30.73	57.7	172	220-240	14.5-15.7	3180-3780	50/60	1	KOREA	

Plumbing: 138-621 kPa. Machines supplied with 3/8" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Single/Dual Filter Pack 20138.1000



Inlet Hose Assembly 32865.1002



Servers and Stands

ThermoFresh® Dual®

TF brewers use Digital Brewer Control™ with insulated ThermoFresh servers that keep bevarages hot without requiring the energy consumption of traditional warming plates

Brews 61.7 to 71.5L of coffee per hour

Three variable batch sizes

BrewWISE® intelligence means compatible grinders and a Smart Funnel® can be programmed one time to manage repeated brewing cycles from start to finish

Stores individual coffee recipes so operator can easily brew many varieties





Dual TF DBC

		DESCRIP	TION				CAPACITY			ELECTRICAL	L			AGENCY
Product #	Model	Finish	Funnel Type	Height 2	imensions « Width x entimeters	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
34600.0011	DUAL TF DBC	STAINLESS	SMART	90.68	55.37	60.5	302	220-240	27-29.5	6000-7100	50-60	1	NO	(€ &
34600.0020	DUAL TF DBC	STAINLESS	SMART	90.68	55.37	57.4	276 414	230 400	33.5 16	8000 11125	50-60 50-60	1	NO	CE (NSF.)

Plumbing: 138-621 kPa. Machines supplied with 3/8" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Single/Dual Filter Pack 20138.1000



Inlet Hose Assembly 32865.1002



Servers and Stands

SmartWAVE® Thermal

BUNN exclusive brewing technology that increases turbulence in the funnel for uniformity of extraction

Adjustable low profile design can accommodate a variety of thermal servers and countertop configurations

Analog switches accompanied by red/green LED for programming and brewing status (Ready, Heating, Brewing)

Choice of 3 pulse brew settings to adjust Flavor profile

Energy Saver Mode reduces tank temperature during idle periods

Specialty

Includes Gourmet C funnel for larger throw weights

Large 17-hole sprayhead maximizes uniformity of extraction



WAVE -S-BF-APS with Airpot



WAVE -S-BF-APS with Gourmet Funnel



WAVE-S-BF-APS with Thermal Carafe on Slide-out Booster Tray

	DE	SCRIPTION		CAPACITY			ELECTI	RICAL			AGENCY
Product #	Model	Funnel Type	Dimensions Height x Width x Depth (Centimeters)	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
39900.0017	WAVE-S-BF-APS SPECIALITY	GOURMET C	47.47 24.66 43.79	84-90	220-240	8.3-9	1800-2200	50-60	1	EURO	Œ

Plumbing: 138-621 kPa. Machines supplied with 1/4" hose thread adapter and fitting. All plumbed models that are CE listed feature backflow prevention.



Regular Filter Pack 20115.0000



SOLD SEPARATELY



Black Plastic Funnel



Gourmet Filter Pack 20157.0001



AXIOM® Thermal Brewers

Medium volume brewing solution featuring Digital Brewer Control™ for precise extraction control

APS Equipment brews directly into 2.5 - 3.8L airpots

Programmable Energy Saver Mode reduces operating cost during idle periods

Cold brew lock-out and automatic warmer time-out ensure high quality, fresh tasting coffee

Front of machine programming simplifies installation

TC equipment brews directly into thermal carafes up to 21.6cm tall







AXIOM-TC

		DESCRIPTION				CAPACITY			ELECTRI	CAL			AGENCY
Product #	Model	Funnel Type	Height	Dimensions x Width x Centimeter	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
38700.0037	AXIOM-APS	BLACK PLASTIC	59.94	22.86	46.99	90	220-240	12.5-13.6	2750-3275	50-60	1	EURO	C€
38700.0074	AXIOM-APS	BLACK PLASTIC	59.94	22.86	46.99	90	230	15.7	3600	50-60	1	AUS	
38700.0104	AXIOM-TC	STAINLESS	45.2	22.9	47.0	80	220-240	6.7-7.3	1475-1750	50-60	1	EURO	C€

Plumbing: 138-621 kPa. Machines supplied with 3/8" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.













Gourmet Filter Packs 20157.0001

CW Airpot

Simple switch controls and flexible server options

CWA

CWA models are pourover only

No faucet

CWTFA

Brew directly into 2.5 to 3.8L airpots

Hot water faucet with pourover backup feature

Digital timer enables users to make cycle adjustments from front panel





CWTFA-APS

	DESCRIPTION	N				CAPACITY			ELECTRI	CAL			AGENCY
Product #	Model	Funnel Type	Height 2	imensio « Width entimete	x Depth	236mL cups/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
					PC	OUROVER - NO	FAUCET						
23001.0024	CWA-APS	BLACK PLASTIC	61.2	22.9	49.5	84-90	220-240	8.6-9.5	1900-2300	50-60	1	EURO	C€
23001.0074	CWA-APS	BLACK PLASTIC	61.2	22.9	49.5	84-90	220-240	8.6-9.5	1900-2300	50-60	1	UK	NSF. CE
					AU ⁻	TOMATIC - WITH	FAUCET						
23001.0021	CWTFA-APS	BLACK PLASTIC	61.2	22.9	54.6	84-90	220-240	8.6-9.5	1900-2300	50-60	1	EURO	NSF. CE

SOLD SEPARATELY

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Inlet Hose Assembly 32865.1001



Gourmet C Funnel 34559.0000



Gourmet Filter Packs 20157.0001

Thermal Carafe

Brew directly into portable insulated servers that keep coffee at optimal temperature profile

Accepts thermal carafe up to 21.6cm

Use in quick-turn environment where high quality coffee is continuously refreshed

Simple switch controls

CWA-TC

Pourover brewer requires no plumbing – completely portable

CWTFA-TC

Hot water faucet and pourover backup feature





	D	ESCRIPTION			CAPACITY			ELECTRICA	L			AGENCY
Product #	Model	Funnel Type	Height x	mensions : Width x Dep ntimeters)	th 236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
				POU	ROVER - NO FAU	CET						
23001.0105	CWA-TC	BLACK PLASTIC	45.47	22.86 46.99	83	220-240	8.6-9.5	1900-2300	50-60	1	EURO	CE

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.





Inlet Hose Assembly 32865.1001



CARAFES

AXIOM® Automatic 3 Warmers

Plumbed, medium volume brewing solution with Digital Brewer Control™ for precise extraction control

Large 5.9L tank provides back-to-back brewing capacity

For high lime areas, $\mathsf{BrewLOGIC}^{\$}$ technology calculates flow rate and adjusts brew time to maintain consistent brew levels

Coffee extraction, brew level, cold brew lock-out and tank temperature controlled with programmable features

Electronic diagnostics and built-in tank drain simplify maintenance and service

Energy Saver Mode





AXIOM-3

		DESC	RIPTION				CAPACITY			ELECTRICA	L			AGENCY
Product #	Model	Warmers	Funnel Type	Height	Dimension x Width x Centimeter	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
38700.0038	AXIOM-3	2 UPPER/ 1 LOWER	STAINLESS	48.01	21.59	54.36	79	220-240	13.2-14.4	2900-3500	50-60	1	EURO	C€
38700.0039	AXIOM-3	2 UPPER/ 1 LOWER	STAINLESS	48.01	21.59	54.36	79	220-240	8.6-9.0	1900-2100	50-60	1	EURO	C€
38700.0004	AXIOM-3	2 UPPER/ 1 LOWER	PLASTIC	48.01	21.59	54.36	79	220-240	8.6-9.0	1900-2100	50-60	1	EURO	C€
38700.0033	AXIOM-3	2 UPPER/ 1 LOWER	PLASTIC	48.01	21.59	54.36	79	220-240	14.2-15.6	3200-3800	50/60	1	CHINA	(1)
38700.0051	AXIOM 1/2 Batch	2 UPPER/ 1 LOWER	STAINLESS	48.01	21.59	54.36	120	200	19	3800	50/60	1	NO	
38700.0055	AXIOM 1/2 Batch	2 UPPER/ 1 LOWER	STAINLESS	48.01	21.59	54.36	58	100	15	1500	50/60	1	NEMA	
38700.0064	AXIOM-3	2 UPPER/	STAINLESS	48.01	21.59	54.36	79	220-240	8.6-9.0	1900-2100	50/60	1	KOREA	

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Regular Filter Pack 20115.0000



Inlet Hose Assembly 32865.1001



Decanters

Automatics with Upper Warmers

Plumbed, medium volume brewing solution with simple switch controls

CWTFA & CWTF35A

SplashGard® funnel deflects hot liquids away from the hand

Plastic or Gourmet C funnel options

Hot water faucet and pourover backup on all models





CWTF-35A

		DESCRI	PTION				CAPACITY			ELECTRIC	AL			AGENCY
Product #	Model	Warmers	Funnel Type	Height :	oimensio x Width entimete	x Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
12950.0277	CWTF35A	2 UPPER/ 1 LOWER	PLASTIC	48.01	21.59	45.21	90	220-240	14.5-15.8	3200-3800	50-60	1	EURO	NSF (E

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Regular Filter Pack 20115.0000



Inlet Hose Assembly 32865.1001



Decanters

Pourover Decanter Brewer 1 Warmer - VP17A-1

Ideal simple switch control office coffee brewer that does not require plumbing or special wiring

Space-saving design; under 45.2cm tall

SplashGard® funnel deflects hot liquids away from the hand

Pourover brewer requires no plumbing – completely portable





VP17A-1

		DESCRIPTION	ı			CAPACITY			ELECTR	RICAL			AGENCY
Product #	Model	Warmers	Height	Dimension x Width x Centimeter	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
13300.0024	VP17A-1	1 LOWER	43.94	21.59	44.96	93	220-240	9-9.9	2000-2375	50-60	1	EURO	C€





Decanters

Pourover Decanter Brewer 2 Warmer - VP17A-2

Ideal simple switch control office coffee brewer that does not require plumbing or special wiring

Two separately controlled warmers

SplashGard® funnel deflects hot liquids away from the hand

Pourover brewer requires no plumbing – completely portable





		DESCRIPTION				CAPACITY			ELECTRIC	CAL			AGENCY
Model	Product #	Warmers	Height	Dimension x Width x Centimeter	Depth	236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
13300.0015	VP17A-2	1 UPPER/ 1 LOWER	48.01	21.59	45.21	104	220-240	9.5-10.4	2100-2500	50-60	1	EURO	Œ



Regular Filter Pack 20115.0000



Titan[®] Dual[®]

High volume solution using fresh ground coffee and featuring Digital Brewer Control™

Increased brewing capacity

Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; variable bypass controls coffee strength

BrewMETER® allows for easy programming of pulse routine

Funnel has 0.8kg capacity and paper filter retainers to eliminate fold-over





		DESCRIPTION				CAPACITY			ELECTRICA	AL			AGENCY
Product #	Model	Dimensions 1odel Funnel Type Height x Width x Depth (Centimeters)			Depth	236mL cups/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
39200.0002	TITAN DUAL	STAINLESS	101.65	90.50	55.22	503 307-366*	400 220-240	16 28-33	11125 6200-8000	50-60 50-60	3	No	(€&

Plumbing: 138-621 kPa. Machines supplied with 3/8" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Single/Dual Filter Pack 20111.0000

Flavor Label 41745.1000



Inlet Hose Assembly 32865.1002



Titan Funnel 40114.0000



11.4L Titan Server 39400.0001



5.7L Titan Server 46300.0000

Urns

Unique urn brewer design ensures low evaporation loss

U3 TWIN

Two spigots



		DESCRIPTION				CAPACITY			ELECTRICA	L			AGENCY
Product #	Dimensions Model Funnel Type Height x Width x Depth (Centimeters)			236mL cups/hr*	Volts	Amps	Watts	Hertz	Phase	Plug	Listing		
20500.0016	U3A	PLASTIC	82.30	87.63	53.34	278	220-240	26.4-28.6	5800-6850	50-60	1	No	C€

Plumbing: 138-621 kPa. Machines supplied with 3/8" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.

SOLD SEPARATELY









Drip Tray (U3) 07284.0000

Inlet Hose Assembly 32865.1001



G Series VH Grinder

Users have 340° of grind resolution on the "no-click" selection dial, giving them complete freedom when dialing-in their ideal grind particle size

Available in .45kg, .91kg, and 1.36kg versions, the GVH features hoppers that are sleek, tinted, and incredibly durable

Versatile design allows grinding into bags, cans, and cups and other containers to meet a multitude of customer needs

Fast grinding – one pound (.45kg) in about 30 seconds – maximizes speed of service

340° dial resolution for precise tuning of grind particle size

Ergonomic clamp for holding smaller size bags and containers in place for hands-free operation

Easy to use cleaning lever for complete removal of coffee from grind chamber ensures the customer gets all the coffee ground for them

Precision Rockwell 65C hard burrs provide consistency, grind after grind

Bag switch prevents grinding before bag/container is in place

Four-year warranty on grinding burrs





GVH-2

GVH-3

		DESCRIPTION	ı			CAPAC	CITY			ELECTRI	CAL			AGENCY
Product #	Model	Finish	Height	Dimension x Width x Centimeter	Depth	Number of Hoppers	Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
55600.0201	GVH-2A TURK BURR	STAINLESS	62.50	17.80	40.40	1	.90	220-240	6.5-7.8	990-1080	50-60	1	EURO	C€
55600.0301	GVH-3A	STAINLESS	65.50	17.80	40.40	1	1.36	220-240	6.5-7.8	990-1080	50-60	1	EURO	C€
55600.0302	GVH-3A	STAINLESS	65.50	17.80	40.40	1	1.36	220-240	6.5-7.8	990-1080	50-60	1	KOREA 10A	
55600.0304	GVH-3A	STAINLESS	65.50	17.80	40.40	1	1.36	220-240	6.5-7.8	990-1080	50-60	1	UK	CE



GVH Hopper 1lb/.45kg



GVH Hopper 2lb/.91kg 54332 1000



GVH Hopper 3lb/1.4kg 54335.1000

Multi-Hopper Series Grinder and Storage System

An intuitive, portion-controlled coffee grinding system that handles multiple bean varieties

Portion-controlled for the right amount of coffee every time, with 3 batch sizes per hopper

Convenient front-loading hoppers are easy to clean and store individual coffee grind weight profiles

Choice of black or stainless finish

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

Grinder adjusts the grind time for each batch to deliver just the right grind volumes

Grinder communicates coffee batch size and coffee name to the Smart Funnel during grinding process

BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee

Rack and Hopper

Store and display coffee varieties and promote fresh ground coffee program

Hoppers with locking lids serve as storage containers when not in the grinder (lock for lids sold separately)



MHGA

DE	SCRIPTION	ı				CAPAC	CITY			ELECTR	ICAL			AGENCY
Product #	Model	Finish	Height	Dimension: x Width x Centimeter	Depth	Number of Hoppers	Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
35600.0021	MHGA	STAINLESS	73.91	23.77	45.72	2	2.72	220-240	6.5	920	50-60	1	EURO	(€
35600.0023	MHGA	BLACK	73.91	23.77	45.72	2	2.72	220-240	6.5	920	50-60	1	EURO	C€
35600.0025	MHG	STAINLESS	73.91	23.77	45.72	2	2.72	100	9	900	50	1	NEMA	
35600.0137	MHGA	STAINLESS	73.91	23.77	45.72	2	2.72	220-240	6.5	920	50-60	1	UK	CE



2 Position Rack 36760 0000



4 Position Rack 36760 0001



Hopper/Lid Assembly 36845.0000

Weight Driven Series Grinder

Weight-based, portion-control for the right amount of coffee every time with three batch sizes

Unparalleled grind weight accuracy

Front-loading, removable hopper is easy to clean

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

Grinder communicates coffee weight to the Smart Funnel during the grinding process

BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee



G9WD-RH

		DESCRIPTION	l			CAPAC	CITY			ELECT	RICAL			AGENCY
Product #	Model	Finish	Height	Dimension x Width x Centimeter	Depth	Number of Hoppers	Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
40700.0132	G9WD-RH	STAINLESS	75.69	20.68	48.26	1	2.72	220-240	6.5	920	50-60	1	EURO	Œ
40700.0137	G9WD-RH	STAINLESS	75.69	20.68	48.26	1	2.72	220-240	6.5	920	50-60	1	UK	$C \in$





Portion Control Series Grinder

Portion controlled for the right amount of coffee every time, with three batch sizes per hopper

Two hoppers hold 2.7kg each of regular, decaf or specialty coffee beans

Three batch sizes per hopper, with individual grind profiles

Compatible with BrewWISE TF, SG, ICB

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

Grinder adjusts the grind time for each batch to deliver just the right grind volumes

Grinder communicates coffee batch size and coffee name to the Smart Funnel during grinding process

BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee



G9-2TA DBC

	D	ESCRIPTION				CAPAC	CITY			ELEC.	TRICAL			AGENCY
Product #	Model	Finish	Height	Dimensions x Width x Centimeter	Depth	Number of Hoppers	Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
33700.0007	G9-2TB DBC	STAINLESS	68.83	21.08	45.72	2	2.72	100	9.4	940	50	1	NEMA	

French Press Portion Control Series Grinder

Portion controlled for the right amount of coffee every time, with three batch sizes per hopper

Accommodates up to 20.3cm tall cafetière or funnel for drip-style brewer

Multi-batch setting allows users to specify a French press brew size or grind enough coffee into a funnel to brew larger amounts of drip-style coffee

Compatible with VP, CW, Axiom, SmartWAVE®

FPG-2 A DBC

Two hoppers hold 1.36kg each of regular and decaf or specialty beans

Digital touch pad for front-of-machine programming and LCD readout



French press for display purposes only, not available for purchase



FPG-2 DBC	FPG.

	D	ESCRIPTION	I			CAPAC	ITY			ELECTR	ICAL			AGENCY
Product #	Model	Finish	Height	Dimension x Width x Centimete	Depth	Number of Hoppers	Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
36400.0132	FPGA-2	STAINLESS	56.90	21.08	25.40	2	1.36	220-240	1.5	360	50-60	1	EURO	
36400.0137	FPGA-2 DBC	STAINLESS	56.90	21.08	25.40	2	1.36	220-240	1.5	360	50-60	1	UK	
36800.0132	FPGA	STAINLESS	51.60	21.08	28.70	1	2.722	220-240	1.5	330-360	50-60	1	EURO	
36800.0137	FPGA SST	STAINLESS	51.60	21.08	28.70	1	2.722	220-240	1.5	330-360	50-60	1	UK	

Bulk Series Grinder

High volume grinding systems with turbo action that draws the coffee through the chamber for greater grinding speed and efficiency

G3A HD

Grinds .45kg in approximately 30 seconds

Wide range of grinds can be selected

Convenient cleaning lever ensures complete clean out of grind chamber



	CAPA	CITY		AGENCY										
Product #	Model	Finish	Height:	Dimensions Height x Width x Depth (Centimeters)			Kg per Hopper	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
22100.0232	G3A HD	BLACK	67.31	18.54	40.64	1	1.36	220-240	6.5-7.8	990-1080	50-60	1	EURO	C€
22100.0023	G3A HD	BLACK	67.31	18.54	40.64	1	1.36	220-240	6.5	990-1080	60	1	KOREA	
22104.0002	G1 HD	BLACK	67.31	18.54	40.64	1	0.45	100	6.5-7.8	990-1080	50-60	1		



Crescendo®

Authentic single-cup espresso served pure, or built into your choice of 9 café beverages

Touchpad features two programmable portion sizes, 8 and 12oz and 9 beverage choices, plus hot water

9 bar brew pressure used with a variable brew group produces an excellent single or double shot with beautiful crema

Engineered with three powder hoppers; two 3.3lb hoppers for the larger demand flavors and a third 2.2lb hopper that allows for additional flavor

Large 2.2 lb hopper displays whole coffee beans to provide the visualization of fresh ground coffee for each cup

Pleasing design with a compact footprint



Crescendo

	CAPACITY			E	LECTRICA	L						
Product #	Model	Dimensions Height x Width x Depth (Centimeters)		Shots/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Agency	
44300.0200	CRESCENDO	79.40	35.90	49.90	40	220-240	11.5-12.2	2500-2900	50hz	1	EURO	C€
44300.0213	CRESCENDO	79.40	35.90	49.90	40	220-240	11.5-12.2	2500-2900	50hz	1	UK	(€

Plumbing: 20-90 PSI. Machine supplied with garden hose fitting.

Sure Immersion®

Fresh, expertly-extracted coffee from an intuitive touchscreen experience

Filter style coffee from a vacuum system with exclusive Air Infusion® extraction control resulting in a clean, balanced cup with a smooth finish

Coffee selections include iced and hot options

Each recipe has programmable air-infusion and immersion control for the Best Result in the Cup™

Dispense fresh coffee in 5 portion sizes, programmable from 6 to 24oz cup, plus carafe

220

2 hoppers and two independent grinders with precision burrs for accurate grind profiles



Sure Immersion® 220

	CAPACITY			EL	ECTRICAL							
Product #	Model	Dimensions Height x Width x Depth (Centimeters)			8oz cups/hr 296mL cups/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Agency
44400.0106	SURE IMMERSION 220	100	40.9	50.3	63	100	13	1300	50/60	1	NO	
44400.0108	SURE IMMERSION 220	100	40.9	50.3	63	200	12	2400	50/60	1	NO	



Infusion Series® Standard Edition Coffee and Tea Combo

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ITCBA

Brews into all BUNN iced tea dispensers (except TDS-5), 1.9 to 3.8L airpots, thermal carafes and can accommodate BUNN® ThermoFresh® Servers

The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup.



ITCBA

	DESCRI	IPTION			CAPACITY COFFEE	CAPACITY TEA	ELECTRICAL						
Product #	Model	Dimensions Height x Width x Depth (Centimeters)			236mL cups/hour	236mL cups/hour	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
52200.0500	ITCBA	88.90	25.65	60.45	120*	337	220-240	13.2-14.1	2900-3400	50-60	1	EURO	C€
52200.0502	ITCBA	88.90	25.65	60.45	120*	337	220-240	13.2-14.1	2900-3400	50-60	1	KOREA	

 $Plumbing: 138-621 \ kPa. \ Machines \ supplied \ with \ 1/4" \ Male \ flare \ fitting. \ All \ plumbed \ models \ that \ are \ CE \ listed \ feature \ backflow \ prevention.$











Stand Assembly, TF Server

Infusion Series® Standard Edition Coffee and Tea Combo High Volume

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

Achieve a variety of flavor profiles and batch options with programmable Digital Brewer Control.

BrewWISE® intelligence with pre-infusion and pulse brew ensures ultimate control of your brewing process and maximum flavor extraction.

The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup

High volume model includes Smart Funnel® for coffee; compatible with BrewWISE® grinders

Large 3gal tank provides back-to-back brewing capacity

Brews into all BUNN Iced tea dispensers (except TDS-5), 2.5 - 3.8L airpots



ITCB-DV HV

	DESCRIP	TION			CAPACITY COFFEE	CAPACITY TEA	ELECTRICAL						AGENCY
Product #	Model	Dimensions Height x Width x Depth (Centimeters)		236mL cups/hour	236mL cups/hour	Volts	Amps	Watts	Hertz	Phase	Plug	Listing	
52300.0500	ITCBA HV CE	88.9	25.4	61.0	336	336	220-240	11.0-12.0	2400-2900	50-60	1	UK	C€

Compatible Dispensers - TD4T, TDS-3, TDO-4, TDO-N-3.5, TDO-N-4 Tea Dispensers, 1 and 1.5gal ThermoFresh® Severs





20138.0000





Airpots and Thermal Carafes

Stand Assembly, TF Server



COLD COFFEE SOLUTIONS



BUNN offers a variety of profitable solutions for your Cold Coffee menu. From fresh-brewed tailored recipes by the batch to cold brew concentrate dispensers for multiple gallons of finished drinks, we have you covered.

PRODUCT	PAGE NUMBER
Infusion Series® Coffee Brewer Family - ICB	5-7
Infusion Series® Tea & Coffee Combo Brewer Family - ITCB	33-34
Nitron ₂ ® Family	37-38
Ultra® Family	46-47

LEARN MORE: bunn.com/cold-coffee

Nitron₂® Cold Draft

Keg-free design delivers authentic Cold Brew taste without need for a complex brewing process

Achieve a nitro infusion with no kegs to change-out, store, clean, or sanitize. Uses two 3.8L concentrate BIBs or BUNN refillable containers (for Ball-valve models) or two 1.9L concentrate BIBs (for Scholle models) that staff are already familiar with and each BIB yields multiple gallons of finished drinks

The Nitron® Experience: No milk or sugar needed! BUNN's exclusive in-line gas infuser produces up to 3 minutes* of cascading micro-bubbles, resulting in a nitro cold brew crowned with a smooth, silky stout-like head that tastes distinctively creamy with a velvety soft mouthfeel

Outfit the standard and nitro taps with separate beverages - your choice of cold brew coffee, iced coffee, or iced tea - all from one slim, 25.4cm wide countertop design

At a rate of one 473ml drink per minute, can dispense 60 drinks before exceeding 5°C

*Results based on product concentrate used



Nitron₂® Cold Draft (All Black Door)

	DESCRIPTION										
Product #	Model	Removable Graphic Door	All Black Door	Temperature Setting °C	Heigh	Dimensions t x Width x Centimeters	Depth	Volts			
51600.0024	NITRON BALL-VALVE EURO 4:1 to 12:1	NO	YES	5	86.36	25.40	72.14	220-240			
51600.0025	NITRON BALL-VALVE UK 4:1 to 12:1	NO	YES	5	86.36	25.40	72.14	220-240			
51600.0034	NITRON ALL-NITRO BALL VALVE 4:1 to 12:1	NO	YES	5	86.36	25.40	72.14	220-240			
51600.0037	NITRON ALL-NITRO SCHOLLE CE 4:1 to 12:1	NO	YES	5	86.36	25.40	72.14	220-240			

Nitron₂® Cold Draft Gas Module

220-240V 50-60Hz NITRON Gas Module CE, UK Plug

Designed to work directly with the Nitron Cold Draft dispenser, the Gas Module accessory is an optional external gas source to be used in place of high-pressure tanks or nitrogen generators. The Gas Module features a built-in multi-stage air filtration system to remove impurities and moisture from the air to assure great tasting Nitro beverages.

Features:

- System design allows for quick access to internal components for ease of service, with just a few hand tools
- Compatible with all Nitron Cold Draft dispensers, the modular unit can be installed under or next to the machine or beneath the counter in a cabinet. Its modular design works with new and existing Nitron dispensers already in service
- PM frequency to replace the internal air filters requires annual schedule with 1 Nitron dispenser and every 6 months when connected to 2 Nitron dispensers
- The Gas Module features integrated multi-stage FDA-compliant filters to remove impurities and moisture from the air
- Compact, space-saving design produces its own unlimited supply of gas for up to two Nitron dispensers, eliminating the need for high-pressure tanks and nitrogen generators
- 220-240V with UK plug for easy set-up and includes 8-feet of gas line with 1/4" female flare fitting (washer included) for quick connection to the Nitron dispenser
- Supports up to two Nitron dispensers



Nitron₂® Cold Draft Gas Module

	DESCRIPTION				ELECTRI	CAL	AGENCY
Product #	Model	Height x V	ensions Vidth x D timeters)	epth	Volts	Plug	Listing
55660.0002	NITRON GAS MODULE 220-240v CE UK Plug	11.9	21.1	37.1	220-240	UK	C€
55660.0003	NITRON GAS MODULE 220-240v CE EURO Plug	11.9	21.1	37.1	220-240	EURO	C€



iMIX® Series

Sleek powdered beverage dispenser delivers hot drinks with exceptional reliability and taste - all from an operator friendly design

iMIX 3

Three 3.6kg hoppers

LED backlit door graphics

Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6g powder per second)

Left or top-hinged door option

Dispense 36 355ml cups in 14 minutes before dropping 5.6°C from first cup serving temperature

Display allows adjustments and service operational testing from front of machine, communicates machine status, technical support contact information,

and advertising messages

Three Sized Portion Control



iMIX-3A

	DESC	RIPTION					ELECTRIC	CAL			AGENCY
Product #	Model	Dimensions Height x Width x Depth (Centimeters)			Volts	Amps	Watts	Watts Hertz Phase			Listing
36900.0014	iMIX-3A	83.31	31.24	61.21	220-240	13.6-14.5	3000-3500	50-60	1	EURO	CE

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



Precise Temperature Medium Volume

Accuracy, adjustability, energy efficiency and styling in a quality hot water dispenser

11.4L tank

Precise temperature control and hot water on-demand to 100°C

Contemporary, low profile design for front-of-house and self-service

Eco-friendly technology maximizes energy use

Thinsulate® tank insulation improves energy efficiency

Programmable "Energy Saver Mode" reduces operating costs during idle periods

LED display provides simple temperature adjustment

Intuitive blue LED dispense button

Cup clearance accommodates a range of serving options for custom-crafted, hand pour coffees and teas



H3XA with 100C

	DESCRIPTION					CAPACITY WATER INPUT 15.6°C			ELECTRIC	AL			AGENCY
Product #	Model	Height	Dimension x Width a entimete	x Depth	Temperature Setting °C	L/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
45300.0000	H3EA Element	49.02	19.3	56.52	96	29.9	220-240	11.5-12.5	2500-3000	50-60	1	UK	C€
45300.0002	H3EA Element	49.02	19.3	56.52	96	29.9	220-240	11.5-12.5	2500-3000	50-60	1	EURO	< € EH[
45300.0004	H3EA Element	49.02	19.3	56.52	96	29.9	220-240	11.5-12.5	2500-3000	50-60	1	KOREA	

Plumbing: 138-621 kPa. Machine supplied with 1/4" BSPP Male flare fitting.



Precise Temperature Medium Volume

Accuracy, adjustability, energy efficiency and styling in a quality hot water dispenser

18.9L tank

Thinsulate® tank insulation provides increased energy efficiency

LED display provides simple temperature adjustment

Digital thermostat provides consistent and accurate temperatures of 15.6°-100°C

Programmable "Energy Saver Mode" reduces operating cost during idle periods







H5XA Element



H5XA Element

(Stairliess)							(vvnice)			(DIACK)				
							CAPACITY							
		DE	SCRIPTIC	ON			WATER INPUT 15.6°C			ELECTRIC	AL			AGENCY
Product #	Model	Height	imension x Width a entimete	x Depth	Finish	Temperature Setting °C	L/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
43600.0002	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	208	19.5	4050	60	1	NO	(PL) LISTED (NSF.)
43600.0003	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	240	16.9	4050	60	1	NO	(NSF.
43600.0013	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	220-240	15.5-16	3400-3800	50/60	1	EURO	< € EH[
43600.0022	H5XA Element	72.40	18.00	44.50	BLACK	100	36.6*	220-240	15.5-16	3400-3800	50/60	1	EURO	C€ EH[
43600.0032	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	220-240	15.5-16	3400-3800	50/60	1	NO	C€
43600.0041	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	220-240	15.5-16	3400-3800	50/60	1	KOREA	
43600.0046	H5XA Element	72.40	18.00	44.50	STAINLESS	100	36.6*	220-240	15.5-16	3400-3800	50/60	1	CHINA	QS complian

Plumbing: 138-621 kPa. Machine supplied with 1/4" OD Male flare fitting.



Inlet Hose



Shelf Kit 12599.0000



Wall Bracket Kit, Side Mount

Constant Temperature Medium Volume

HW2A

Space-saving machine just 18cm wide to fit any counter

High quality, easy-to-clean stainless steel exterior and tank for a long life

Includes drip tray

H5E/EA PC

Three programmable volume settings and one push and hold continuous dispense button







H5E/EA PC

	1	DESCRIPTION	NC			CAPACITY			ELECTRICA	\L			AGENCY
Product #	Model	Height	Pimension x Width : entimete	x Depth	Temperature Setting °C	L/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
02500.0002	HW2A	60.96	18.03	36.32	93.3	19.3	220-240	7.3-7.9	1600-1900	50-60	1	EURO	C∈ EHI
39100.0003	H5EA PC	72.14	17.78	39.37	18.3-96.1	40.1	220-240	15.5-16	3400-3800	50-60	1	EURO	C€ ENI

SOLD SEPARATELY



Inlet Hose Assembly





Ultra® Series

Frozen beverage dispenser with reversing auger technology for superior mixing and freezing

Manual Fill

Two 11.36L hoppers

Pour water and product mix directly into hopper; special plumbing not required

Torque sensor technology maintains consistent product thickness for superior beverages

Reversing auger insures product quality and product presentation in the hopper

High efficiency LED lighting



Ultra-2A

		DESCR	IPTION					ELEC1	RICAL			AGENCY
Product #	Model	Height	Dimensions t x Width x Centimeter	Depth	Finish	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
34000.0002	ULTRA-2A	81.28	40.64	62.23	BLACK	220-240	4.7-5.1	1050-1100	50-60	1	EURO	CE (NSF)
34000.0003	ULTRA-2A	81.28	40.64	62.23	STAINLESS/WHITE	220-240	4.7-5.1	1050-1100	50-60	1	EURO	CE (NSF)
58000.0041	ULTRA NXA	81.28	40.64	62.23	BLACK	230	4.7-5.1	1050-1100	50	1	EURO	CE (NSF)
58000.0048	ULTRA NXA	81.28	40.64	62.23	BLACK	230	4.7-5.1	1050-1100	50	1	UK	((NSE)

SOLD SEPARATELY



ULTRA-2 Hopper Group 34000.0402, 34000.0403

Ultra® Series

Frozen beverage dispenser with reversing auger technology for superior mixing and freezing

Two 11.36L hoppers

High efficiency LED lighting

Torque sensor technology maintains consistent product thickness for superior beverages

Reversing auger insures product quality and product presentation in the

Liquid Autofill

Liquid Autofill product hoppers automatically replenish

Designed to be used with Brix Pumps

CV Value Autofill

Constamt flow control for accurate brixing of product; Internal brixing allows interface with standard BIB pumping



		DESC	RIPTION	ı					ELECTRICA	L			AGENCY
Product #	Model	Height	Dimension x Width entimete	x Depth	Finish	CF Valve	Volts	Amps	Watts	Hertz	Phase	Plug	Listing
58000.0040	ULTRA NXA LIQUID AUTOFILL	81.28	40.64	62.23	BLACK		230	4.7-5.1	1050-1100	50	1	EURO	C€
58000.0042	ULTRA NXA CFV LIQUID AUTOFILL	81.28	40.64	62.23	BLACK		230	4.7-5.1	1050-1100	50	1	EURO	Œ
58000.0044	ULTRA NXA LIQUID AUTOFILL	81.28	40.64	62.23	BLACK		230	4.7-5.1	1050-1100	50	1		Œ

Plumbing: 138-621 kPa. Machines supplied with 1/4" Male flare fitting. All plumbed models that are CE listed feature backflow prevention.



ThermoFresh® Digital Gauge Servers

Holds temperature for hours without traditional warming plates

TF Server

Digital timer begins to count up in one minute increments to specifically display how long the brewed beverage has been stored; requires four AAA batteries; display shows low battery symbol

Brew-thru lid design also features a pour spout for easy emptying and cleaning

TF Server without Stand

Ideal with Infusion Series® Coffee Brewer (ICB)

TF Server Stand

Use for easy dispensing; 17.9cm cup clearance

Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels



3.8L TF Server without Stand



TF Server Stand



3.8L TF Server (Stand included)

					DIGITAL GUAGE	SERVERS			
Product #	Model	Height	Dimension x Width x Centimeter	Depth	Holding Capacity	Includes Stand	Finish	Compatible Brewers	Agency
42700.0200	TF Server DSG3	52.58	23.62	33.02	3.8L	YES	STAINLESS/ BLACK	Single TF DBC, Dual TF	
42750.0200	TF Server DSG3	57.66	23.62	33.02	5.7L	YES	STAINLESS/ BLACK	DBC, ICB ITCB, ITCB HV	(NSE)
42700.0250	TF Server DSG3	32.00	23.11	32.26	3.8L	NO	STAINLESS/ BLACK	ICB	Mar
42750.0250	TF Server DSG3	37.34	23.11	32.26	5.7L	NO	STAINLESS/ BLACK	ICB Twin	
54473.1000	TF Server Stand	24.64	23.50	33.02	N/A	N/A	BLACK	TF Servers Without Stand	

ThermoFresh® Mechanical Gauge Servers

Holds temperature for hours without traditional warming plates

TF Server

Glass sight gauge on front of server allows for visible indication of level capacity

Brew-thru lid design also features a pour spout for easy emptying and cleaning

Translucent faucet guard for visibility while dispensing

TF Server without stand

Ideal with Infusion Series® Coffee Brewer (ICB)

TF server stand

Use for easy dispensing; 17.9cm cup clearance

Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels

TITAN TF SERVER

11.4L or 5.7L capacity

Insulated and portable

Large cup clearance for a variety of dispensing options



3.8L TF Server



TF Server Stand



TF Server Stand



5.7L TF Server (Stand included)

				М	ECHANICAL GAUGE	SERVERS			
Product #	Model	Height	Dimension x Width x Centimete	Depth	Holding Capacity	Includes Stand	Finish	Compatible Brewers	Agency
44000.0200	TF SERVER	52.83	23.62	33.02	3.8L	YES	STAINLESS/ BLACK		
44000.0201	TF SERVER WITH TIMER	52.83	23.62	33.02	3.8L	YES	STAINLESS/ BLACK	SINGLE TF DBC DUAL TF DBC, ICB	
44050.0200	TF SERVER			33.02	5.7L	YES	STAINLESS/ BLACK	ITCB ITCB HV	(NSF.)
44050.0203	TF SERVER			33.02	5.7L	YES	BLACK		
44000.0250	TF SERVER	32.04	23.11	30.15	3.8L	NO	STAINLESS/ BLACK		
44050.0250	TF SERVER	37.30	23.11	30.15	5.7L	NO	STAINLESS/ BLACK	ICB ICB TWIN	
44050.0251	TF SERVER	37.30	23.11	30.15	5.7L	N/A	BLACK		
46300.0000	TITAN TF SERVER	58.2	29.7	38.9	5.7L	N/A	STAINLESS	TF, ICB SERVERS	
54473.1000	TF SERVER STAND	24.64	23.50	33.02	N/A	N/A	BLACK	N/A	
39400.0001	TITAN TF SERVER	60.2	35.1	43.9	N/A	N/A	STAINLESS	TITAN	

Infusion Series® Soft Heat® Server System

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

SH Server

5.7L capacity; choose from five optional holding time settings

Safety-Fresh® brew-thru lid with vapor seal and spill prevention

Soft grip handle for secure portability

SH Docking Station

Remote one and two server docking stations with 10.2cm legs

Instant power contact with servers

Add additional remote stations to increase volume



1 SH Server and Docking Station

		DESCRIPTION				ELECTRICAL
Product #	Model	Finish	Hei	Dimensions ght x Width x De (Centimeters)	pth	Volts
27850.0200	INFUSION SERIES® 5.7L SH SERVER	BLACK/STAINLESS	36.70	23.00	33.70	N/A
27850.0213	INFUSION SERIES® 5.7L SH SERVER	BLACK	36.70	23.00	33.70	N/A
27825.0300	INFUSION SERIES® 1SH DOCKING STAND	STAINLESS	23.62	25.91	29.97	220-240

Soft Heat® Server System

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

SH Server

5.7L capacity; choose from five optional holding time settings

Soft grip "bail" handle for secure portability

SH Docking Station

Remote one and two server docking stations with 10.2cm legs

Instant power contact with servers

Add additional remote stations to increase volume



1 SH Server and Docking Station

	SOFT HEAT SERVER SYSTEMS														
Product #	MODEL	Height	imensio x Width entimete	x Depth	Holding Capacity	Setting	Finish	Volts	Amps	Watts	Hertz	Phase	Plug	Compatible Brewers	Agency
<u>27850.0001</u>	SH SERVER	42.16	21.59	35.56	<u>5.7L</u>	INFINITY TMR/83C	STAINLESS/ BLACK			Infinity Tmr/83C				CINICLE CIT	
27850.0004	SH SERVER	42.16	21.59	35.56	5.7L	INFINITY TMR/83C	BLACK			Infinity Tmr/83C				SINGLE SH DBC DUAL SH	(NSF.)
27850.0023	SH SERVER	42.16	21.59	35.56	5.7L	INFINITY TMR/91.5C	STAINLESS/ BLACK			Infinity Tmr/91.5C				DBC SINGLE SH DUAL SH	(UL) LISTED
27850.0046	SH SERVER	42.16	21.59	35.56	3.8L	60 MIN/83C	STAINLESS/ BLACK			N/A				DUAL 3H	
27825.0001	1SH DOCKING STATIONS	34.42	25.65	33.53	1 SH SERVER	N/A	STAINLESS	220-240	0.33- 0.36	70-85	50-60	1	EURO	1 SH SERVER	CE (NSE)

Thermal Carafes, Pitchers and Airpots

Thermal Carafe

Highly durable stainless steel interior and exterior

Thermal Pitcher

Stainless steel lining ensures hot coffee for hours

Lever-Action Airpot

Brew-thu lid with lever-action for easy use





Vacuum Pitcher

Lever-Action Airpot





Seamless Thermal Carafe

Thermal Carafe

	CARAFES										
Product #	Model	Capacity	Liner	Lid Color	Quantity per Case	Compatible Brewers	Agency				
36029.0001	DELUXE THERMAL CARAFE	1.9L	STAINLESS STEEL	BLACK	1						
36029.0000	DELUXE THERMAL CARAFE	1.9L	STAINLESS STEEL	BLACK	12						
36252.0001	DELUXE THERMAL CARAFE	1.9L	STAINLESS STEEL	ORANGE	1						
36252.0000	DELUXE THERMAL CARAFE	1.9L	STAINLESS STEEL	ORANGE	12	SMARTWAVE	(NSF.)				
51746.0001	SEAMLESS THERMAL CARAFE	1.9L	STAINLESS STEEL	BLACK	1	CWTF-TC	(NOT.)				
51746.0101	746.0101 SEAMLESS THERMAL CARAFE 1.9L STAINLESS STEEL		STAINLESS STEEL	BLACK	12						
51746.0006	SEAMLESS THERMAL CARAFE	1.9L	STAINLESS STEEL	ORANGE	1						
51746.0007	SEAMLESS THERMAL CARAFE	1.9L	STAINLESS STEEL	GREEN	1						
PITCHERS											
Product #	Model	Capacity	Liner	Quantity	per Case	Brewers	Agency				
39430.0000	VACUUM	1.9L	STAINLESS STEEL		1	SMARTWAVE	(NSF.)				
39430.0100	VACUUM	1.9L	STAINLESS STEEL		6	SMARTWAVE					
			AIRP	OTS							
Product #	Model	Capacity	Liner	Qua	ntity per Case	Brewers	Agency				
32125.0000	LEVER-ACTION	2.5L	STAINLESS STEEL	EL 1							
32125.0100	LEVER-ACTION	2.5L	STAINLESS STEEL		6	CW-APS ICB	Intertek				
32130.0000	LEVER-ACTION	3L	STAINLESS STEEL		1	ICB TWIN SMARTWAVE	intertek				
32130.0100	LEVER-ACTION	3L	STAINLESS STEEL		6	CWTF-APS CWTF TWIN APS					
	LEVER-ACTION	3.8L	STAINLESS STEEL		1	ITCB AXIOM APS	(NSF.)				
36725.0000	2272171011011					ANIONIAIS					
36725.0000 36725.0100		3.8L	STAINLESS STEEL		6	ANOMAIS					

Universal Airpot Racks

Versatile merchandising system for airpots

Displays can be combined or taken apart easily for greater flexibility

Sturdy, carbon-steel wire construction with vinyl coating resists corrosion, easy to clean

Configurations available for two to six airpots



UNIV-2 APR



UNIV-3 APR



UNIV-4 APR

	A	IRPOT RACKS			
Product #	Model	He	Dimensions ight x Width x De (Centimeters)	Capacity	
35728.0000	UNIV-2 APR (1 Upper, 1 Lower)	35.81	19.05	61.21	TWO AIRPOTS
35728.0001	UNIV-2 APR (2 Lower)	17.53	37.85	28.45	TWO AIRPOTS
35728.0002	UNIV-3 APR (3 Lower)	17.53	58.17	28.45	THREE AIRPOTS
35728.0003	UNIV-4 APR (2 Upper, 2 Lower)	35.56	37.85	63.25	FOUR AIRPOTS
35728.0004	UNIV-5 APR (3 Upper, 2 Lower)	35.56	58.17	63.25	FIVE AIRPOTS
35728.0005	UNIV-6 APR (3 Upper, 3 Lower)	35.56	58.17	63.25	SIX AIRPOTS

Iced Tea and Iced Coffee Dispensers

Solid stainless construction stands up to demands of foodservice environments

Sump dispense valves assure complete dispensing of beverage

Variety of shapes and sizes for every counter configuration









5 1 . "			"	NARROW	_	•
Product #	Model	Capacity	Handles	Additional Feature	Brewers	Agency
39600.0001	TDO-N-3.5	13.2L	FRONT/BACK	STANDARD FAUCET, SOLID LID		
39600.0031	TDO-N-3.5	13.2L	FRONT/BACK	LIFT HANDLE, SOLID LID		
39600.0002	TDO-N-4.0	15.1L	FRONT/BACK	STANDARD FAUCET, SOLID LID		
43900.0001	TD3T-N	11.4L	FRONT/BACK	LIFT HANDLE, BREW-THRU LID		
39600.0047	TDO-N-3.5	13.2L	FRONT/BACK	PINCH TUBE, SOLID LID	TALL MODELS W/ 73.66CM TRUNK:	
39600.0059	TDO-N-3.5	13.2L	FRONT/BACK	PINCH TUBE, SOLID LID	TB3, ITCB, ITCB HV	(NSE)
39600.0081	TDO-N-3.5	13.2L	FRONT/BACK	STANDARD FAUCET BREW-THRU LID		
39600.0083	TDO-N-3.5	13.2L	FRONT/BACK	BREW-THRU LID, PINCH TUBE		
39600.0065	TDO-N-3.5	13.2L	FRONT/BACK	HEM		
39600.0066	TDO-N-2.0	7.8L	FRONT/BACK	HEM	SHORT MODELS	
				SQUARE	W/ 65.41CM TRUNK: TB3, ITCB	
03250.0005	TD4T	15.1L	SIDE	BREW-THRU LID, TALL	SHORT MODELS W/ 65.41CM TRUNK: TB3, ITCB	
			CYL	INDER - ROUND		
33000.0000	TDS-3	11.4L	SIDE	STAINLESS LID	TB3 ITCB	
33000.0023	TDS-3.5	13.2L	SIDE	STAINLESS LID	ITCB HV	
			CY	LINDER - OVAL		
34100.0000	TDO-4	15L	SIDE	SOLID, PLASTIC LID		NSF.
34100.0002	TDO-4	15L	SIDE	BREW-THRU PLASTIC LID	TB3	_
34100.0001	TDO-5	18.9L	SIDE	SOLID, PLASTIC LID	ICB ITCB DV	
34100.0003	TDO-5	18.9L	SIDE	BREW-THRU PLASTIC LID		

BREW-THRU PLASTIC LID

SIDE

37100.0000

TDO-3.5 LP

13.2L

(NSF.)

Coffee Decanters

EASY POUR®

BUNN® exclusive design; high quality stainless steel base with drip proof, fast-pour lip

Clear, impact-resistant material complies with FDA regulations for food contact

Glass decanters

Reliable, shatter-resistant, and perfectly balanced with laboratory-grade, stress-free glass





Easy Pour®

		DECANTERS				
Product #	Model	Capacity	Handle Color	Quantity Per Case	Brewers	Agency
06100.0101	EASY POUR	1.9L	BLACK	1		
06100.0102	EASY POUR	1.9L	BLACK	2		
06100.0103	EASY POUR	1.9L	BLACK	3		
06100.0106	EASY POUR	1.9L	BLACK	6		
06100.0112	EASY POUR	1.9L	BLACK	12		
06100.0124	EASY POUR	1.9L	BLACK	24		
06100.0401	EASY POUR with RFID	1.9L	BLACK	24		
06101.0101	EASY POUR	1.9L	ORANGE	1		
06101.0102	EASY POUR	1.9L	ORANGE	2	Decanter Brewers	
06101.0103	EASY POUR	1.9L	ORANGE	3	VP17 AXIOM	
06101.0124	EASY POUR	1.9L	ORANGE	24	CW	
42400.0024	GLASS	1.9L	BLACK	24		
42400.0101	GLASS	1.9L	BLACK	1		
42400.0103	GLASS	1.9L	BLACK	3		
42400.0203	GLASS with RFID	1.9L	BLACK	3		
42401.0024	GLASS	1.9L	ORANGE	24		
42401.0101	GLASS	1.9L	ORANGE	1		
42401.0103	GLASS	1.9L	ORANGE	3		
42401.0203	GLASS with RFID	1.9L	ORANGE	3		



Paper Filters

Selection of coffee filters is a vital step in brewing perfect coffee - don't settle for anything less than BUNN® quality coffee filters. Using the results of years of research, BUNN manufactures the best filters from high quality, heavy weight paper, so the water flows properly through the coffee. Our filters are uniquely designed for strength with taller walls to help reduce overflow and grounds in your coffee.



BUNN's paper stock used in the manufacturing of our coffee filters is produced using an elemental chlorine-free (ECF) bleaching method.

BUNN Paper Filter materials meet:

Restrictive limits as stated in Resolution ResAP(2002)1 on paper and board materials intended to come into contact with foodstuff.

Compositional and end product requirements stated in the Dutch legislation "Regeling Verpakkingen en gebruiksartikelen, Chapter II, Paper and board, pt 2 Paper and board used as cooking paper and for filtering above 80°C".

Limits stated in the German recommendation BfR XXXVI Paper and board for food contact and the special requirements in BfR XXXVI/1 for Cooking Papers, hot filter papers and filter layers.

Product #	Filter Type	Description	Number per Bag	Bags per Case	Number Cluster	Overall Measure x Base Diameter (millimetres)	Packed per Case	Case Weight (kg)	Cases per Skid/Tier
20115.0000	DECANTER FILTERS	REGULAR C, S, R, O, VLPF, VPR, VPS, VP-17	500	2	50	247.65 x 107.95	1000	1.91	180/15
20122.0000		REGULAR FAST FLOW C, S, R, O, VLPF, VPR, VPS, VP-17	500	2	50	247.65 x 107.95	1000	2.04	180/15
20109.0000		URN - U3, SRU, IC-3	252	1	36	450.85 x 184.15	252	2.49	88/11
20124.0000		URN, 11.4L	252	1	36	482.6 x 184.15	252	2.77	88/11
20111.0000	URN	TITAN, URN	252	1	36	508 x 196.85	252	2.99	84/12
20125.0000	FILTERS	URN, 22.7L	250	1	25	533.4 x 222.25	250	3.4	72/9
20113.0000		URN, 37.9L	250	1	25	603.25 x 222.25	250	4.22	54/9
20131.0000		URN, 37.9L	252	1	36	615.95 x 273.05	252	4.40	36/6
20120.0000		SYSTEM III	252	2	36	384.18 x 136.53	504	3.86	108/12
20100.0000	OTHER	TEA BREWERS, SINGLE & DUAL COFFEE BREWERS, 5.7L URNS, SYSTEM II	500	1	50	384.18 x 133.35	500	2.13	150/15
20138.1000	FILTERS	GOURMET, SINGLE TF, DUAL TF, SINGLE SH, DUAL SH, SINGLE, DUAL, 5.7L URNS, ITCB	500	1	36	349.25 x 133.35	504	2.49	108/12
20157.0001		GOURMET C FUNNEL	500	2	50	349.25 x 133.35	1000	3.74	60



Accessories and Cleaning Agents



Cleaning Tablets

	CLEANING AGENTS AND ACCESSORIES		
Part #	Model	Quantity Per Case	Volts
29875.0000	FLOWJET® SYSTEM	ONE	120
29875.0001	FLOWJET® SYSTEM	ONE	230
24634.0000	KAY-5 SANITIZER	200 PACKETS	
24634.0001	KAY-5 SANITIZER	50 PACKETS	
36000.1188	CAFIZA CLEANING TABLETS	TWELVE CONTAINERS	
36000.1189	CAFIZA CLEANING TABLETS (100 COUNT)	ONE CONTAINER	
37306.0000	URNEX DESCALER	ONE 10Z PACKET	
39159.0004	GRINDZ GRINDER CLEANER	TWELVE BOTTLES	
39265.0000	SURE TAMP® STEAM RINZA MILK CLEANER	ONE BOTTLE	
39265.0001	SURE TAMP STEAM RINZA MILK CLEANER	SIX BOTTLES	
39302.0000	REFILLABLE CONTAINER ASSEMBLY	ONE	
39637.0002	TABZ BREWER CLEANER	ONE CONTAINER	
39637.0003	TABZ BREWER CLEANER	TWELVE CONTAINERS	
55605.0000	CAFIZA -CRESCENDO- CLEANING TABLETS (32/BOX)	ONE	

Stock Funnels



URN FUNNEL

07022.0012 PRODUCT NUMBER

For use with U3 brewers

BLACK PLASTIC SPLASHGARD® FUNNEL WITH DECALS

PRODUCT NUMBER 20583 0003



For use with CDBC, CWT, AXIOM®, Smart WAVE® Brewers

PRODUCT NUMBER 29351.0001

> For use with O, R, CDBD Twin, CWT Twin and AXIOM® Twin Brewers



BLACK PLASTIC ITCB FUNNEL

PRODUCT NUMBER 53463.0038

For use when brewing coffee with new Infusion Series® ITB and ITCB Brewers



PRODUCT NUMBER 20216.0000

> For use with CDBC, CWT AXIOM® and Smart WAVE® brewers

PRODUCT NUMBER 20217.0000

For use with O, R, CDBC Twin, CWT Twin and AXIOM® brewers



STAINLESS STEEL SINGLE/DUAL FUNNEL

PRODUCT NUMBER 20201 1201

For use with older Single®, Dual®, and Soft Heat® brewers



SMART FUNNEL®

PRODUCT NUMBER 32643.0000

Standard w/ bypass

PRODUCT NUMBER 32643.0010

w/D-Ring basket

For use with older BrewWISE®, ThermoFresh®, Soft Heat®, DBC® and ICB brewers



SST PLATINUM FUNNEL

PRODUCT NUMBER 54675.0008

> For use with new Infusion Series® Brewers



TITAN® FUNNEL

PRODUCT NUMBER 40114.0000

For use with Titan® brewers

GOURMET C FUNNEL

PRODUCT NUMBER 34559.0000

For use with CDBC, CWT AXIOM® and SmartWAVE® APS and TC brewers

34559 0001 PRODUCT NUMBER

For use with CDBC Twin, CWT Twin and AXIOM® Twin and TC brewers

Universal design – handle may be moved to appropriate side

Allows brewing heavier throw weights

PRODUCT NUMBER 34559.0003

For use with older ITCB

TRANSLUCENT COFFEE FUNNEL

PRODUCT NUMBER 20583.0002

For use with VP and CWTF brewers

PRODUCT NUMBER 29351.0000

For use with O, R, CDBC Twin, CWT Twin and AXIOM® Twin brewers

TRANSLUCENT TEA FUNNEL

PRODUCT NUMBER 03021.0016

For use with SmartWAVE® brewer

TRANSLUCENT TEA FUNNEL

ITCB brewers

For use with TB3Q, TU3Q, and

TRANSLUCENT DUAL DILUTION

03021 0004

03021.0005

(Quick Dispense)





older ITB brewers

TEA FUNNEL PRODUCT NUMBER 03021 0013

PRODUCT NUMBER

For use with TB6 brewer

PRODUCT NUMBER 03021.0014

For use with TB6O brewer

TRANSLUCENT TEA FUNNEL

PRODUCT NUMBER 53463.0039

> For use with new Infusion Series® ITCB Brewers





Special Purpose Funnels

Drip Trays Coffee



TRANSLUCENT POUCH PACK FUNNEL

PRODUCT NUMBER 35282.0001

FOR USE WITH TU3Q BREWER

PRODUCT NUMBER 35282.0002

FOR USE WITH TU3 AND TB3 BREWERS

USE WITH RECTANGULAR TEA POUCH PACK



POUCH PACK FUNNEL FOR **SATELLITE BREWERS**

PRODUCT NUMBER 35282,0000

FOR USE WITH OLDER SINGLE AND DUAL SH BREWERS



POUCH PACK FUNNEL FOR SATELLITE BREWERS

29151.0000 PRODUCT NUMBER BLACK HANDLE

29151.0001

PRODUCT NUMBER ORANGE HANDLE

INTERCHANGEABLE HANDLE ALLOWS USE WILL ALL BUNN DECANTER BREWERS



POUCH PACK FUNNEL FOR **SMALL BREW CHAMBER BREWERS**

PRODUCT NUMBER 02073.0010

FOR USE WITH O AND R BREWERS

PRODUCT NUMBER 02774.0010 BROWN

PRODUCT NUMBER 02774.0011 BLACK FOR USE WITH VP AND CWTF BREWERS



NOTE: Only funnels #35282.0001, #35282.0002, and

#35282.0000 on this page are designed with SplashGard®

to help deflect hot liquids away from the hand.

POUCH PACK FUNNEL FOR LARGE BREW CHAMBER BREWERS

PRODUCT NUMBER 02074.0010

FOR USE WITH O AND R BREWERS

PRODUCT NUMBER 04274 0010 BROWN PRODUCT NUMBER 04274.0012 BLACK

FOR USE WITH VP AND CWTF BREWERS



SH BREWERS AND SH STAND

PRODUCT NUMBER 53452.0001



RWS1 WARMER

PRODUCT NUMBER 20213.0103

INFUSION SERIES® TWIN SH BREWERS AND 2 SH STAND



PRODUCT NUMBER 53452.0000



DUAL® BREWERS

PRODUCT NUMBER 20213.0101



LCR-3 HV

PRODUCT NUMBER 41656.0000





AIRPOT RACK

PRODUCT NUMBER 25368.0000 TRAY

25367.0000 TRAY PRODUCT NUMBER

LINER

38931.0000 TRAY



38932.0000

PRODUCT NUMBER TRAY COVER



U3 COFFEE URN

PRODUCT NUMBER 07284.0000





Drip Trays Dispensed Water



HW2, H5M, and H5X

PRODUCT NUMBER 02497.0000

онw

PRODUCT NUMBER 02497.0001

Drip Trays Tea



TCD AND TDO

PRODUCT NUMBER 38029.1000



TDO-N

39626.0000 TRAY PRODUCT NUMBER

39627.0000 PRODUCT NUMBER TRAY COVER

Drip Trays Hot Dispensed



FMD-1 AND FMD-2

PRODUCT NUMBER 02571.0000 TRAY

28966.0000 PRODUCT NUMBER TRAY COVER FMD-3



PRODUCT NUMBER

28699.0000 TRAY

PRODUCT NUMBER

28267.0000 TRAY COVER



FMD-4 AND FMD-5

PRODUCT NUMBER 34716.0000 TRAY

PRODUCT NUMBER

34717.0000 TRAY COVER



PRODUCT NUMBER 36984.0000 TRAY

PRODUCT NUMBER

36985.0000 TRAY COVER



IMIX-4 AND IMIX-5

PRODUCT NUMBER 36670.0000 TRAY

36739.0000 PRODUCT NUMBER TRAY COVER

Drip Trays Cold Dispensed



JDF-2S PRODUCT NUMBER

JDF-2S/NITRON EXTENDED

38765.1000

44015.1001 PRODUCT NUMBER

INCREASES CUP CLEARANCE TO 10.25"

JDF-4S AND LCR-3

PRODUCT NUMBER 38764.1001



JDF-4S EXTENDED

PRODUCT NUMBER 40789.1000

INCREASES CUP CLEARANCE TO 10.25"

Drip Trays Frozen Dispensed



ULTRA-2 WHITE

28086.0000 TRAY PRODUCT NUMBER

32068.0000 PRODUCT NUMBER TRAY COVER



ULTRA-2 BLACK

PRODUCT NUMBER 28086.0001 TRAY

32068.0001 PRODUCT NUMBER TRAY COVER

Nitron,® Accessories



REFILLABLE CONTAINER ASSEMBLY

PRODUCT NUMBER 39302.0000

NITRON SCHOLLE QUICK CONNECT

55324.0000 PRODUCT NUMBER

NITRON SCHOLLE QUICK CONNECT

PRODUCT NUMBER 55325.0000

Clean Contact Solutions



ANTI-MICROBIAL FILM

Covers your common contact points and allow your equipment to function normally and won't leave a sticky residue when replaced. EPA registered and NSF approved for food and water contact

ANTI-MICROBIAL PARTS

Anti-microbial replacement parts for high-frequency contact points such as faucets, handles and dispense membrane switches. Please contact your BUNN Sales representative for availability.



FAUCET ADAPTERS

Your existing equipment and servers can be part of a clean contact beverage program. Stainless-steel faucet adapters attach to BUNN Soft Heat®, ThermoFresh®, and tea dispensers, allowing for easy cup-push service.



PUSH-STYLE FAUCETS

BUNN servers, new or old, can be outfitted with push-style faucets that emphasize clean contact. These faucets are easy to install and require little effort to dispense.



TAP-KINS™

Tap-Kins are biodegradable and recyclable sleeves that users can easily take from a dispenser, slide over any handle, and discard without any direct surface contact.

FAUCET ADAPTERS	DES	SCRIPTION						
Product #	Model	Finish	Height	Dimensions Height x Width x Depth (Inches)				
57483.0000	PLASTIC FAUCET PUSH HANDLE	BLACK	5.5	2.3	1.5			
57516.0000	PINCH TUBE FAUCET ADAPTER	STAINLESS						
FAUCET ADAPTERS	DES	SCRIPTION						
Product #	Model		Finish					
57480.0000	SST ADAPTER		STAINLES	SS				
57514.0000	SST ADAPTER WITH PEDAL HANDLE		STAINLES	SS				
57509.0000	SST ADAPTER WITH WIRE FORM		STAINLES	SS				

VirtualTOUCH™

A Touchless Beverage Selection & Dispensing Solution

VirtualTOUCH FOR SURE IMMERSION

Touchless coffee experience via smartphone.

Access to full beverage menu with intuitive step-by-step instructions to reduce shared contact points

Powered by BUNNlink®, a cloud-based solution (BUNNlink hardware and annual subscription required. Contact your BUNN sales rep for more information.)

VirtualTOUCH FOR CRESCENDO

The operator selects and dispenses a beverage by hovering a fingertip in front of a selection button without touching the machine.





VirtualTOUCH® ready







VirtualTOUCH® ready

-			_I _	R
	resc	:en	ıac) ~

	DESCRIPTION CA							EL	ECTRICAL			
Product #			8oz cups/hr 296mL cups/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Agency		
44400.0106	SURE IMMERSION 220	100	40.9	50.3	63	100	13	1300	50/60	1	NO	
44400.0108	SURE IMMERSION 220	100	40.9	50.3	63	200	12	2400	50/60	1	NO	
	DESCRIPTION								ELECTRICA	AL		
Produc	Product # Model		Dimensions			Volts	Amns	Watts	Hertz	Phase	Plug	Agency

Product #	Model	Dimensions Height x Width x Depth (Centimeters)		Shots/hr	Volts	Amps	Watts	Hertz	Phase	Plug	Agency	
44300.0200	CRESCENDO	79.40	35.90	49.90	40	220-240	11.5-12.2	2500-2900	50hz	1	EURO	Œ
44300.0213	CRESCENDO	79.40	35.90	49.90	40	220-240	11.5-12.2	2500-2900	50hz	1	UK	C€

Plumbing: 20-90 PSI. Machine supplied with garden hose fitting.

INFUSION SERIES

PRECISE CONTROL BATCH BREWING



The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup.

USB recipe programming.

Accommodates a variety of server types.

