

BUNN refresh®

Cold Water



Still and sparkling premium quality water

bunn.com/refresh

DRINKING WATER FILTER SYSTEM - BUNN Easy Clear® EQHP-5C

Up to 5,000 gallons

SEDIMENT REDUCTION

Reduction of particulate and abrasive hard particles helps prevent equipment wear and to extend the life of pumps, valves, o-rings, and seals.

LEAD REDUCTION

Reduction of lead (Pb) found in distribution lines, lead pipes, lead solder, brass fixtures and lead lined tanks in water coolers.

ACTIVATED CARBON FILTER

Reduction of chloramines and chlorine taste and odor that can impart off-flavors and can be corrosive to wet surfaces, thereby decreasing maintenance costs and increasing equipment life.

NSF 53 FOR CYST REDUCTION*

* Reduction of up to 99.99% of cyst and common water-borne bacteria (E.Coli) by membrane filtration as tested by manufacturer.

Additional Benefits:

- Certified by NSF to Standard 53 for reduction of cyst and lead
- Certified to Standard 42 for the reduction of particulate, chloramines, chlorine taste and odor
- FDA CFR-21 compliant materials. Sanitary Quick Change (SQC) encapsulated cartridge design allows for fast and easy cartridge change-outs with ¼" turn

A FORMULA FOR REFRESHING SPARKL

1 PURITY

BUNN refresh includes a water filter system that achieves a high level of purity certified to NSF Standard 53 for the reduction of cyst and lead, and Standard 42 for the reduction of particulates, chloramines, and chlorine taste and odor. It also reduces up to 99.99% of common water-borne bacteria¹.

With BUNN refresh, clean water taste and quality are right at your finger tips.



2 TEMPERATURE

Ice bank cooling technology and recirculation loop ensures cold water is continuously circulating throughout the system, from the ice cold water reservoir to the faucet, for consistent 40°F water each and every time.


Colder drink temperatures and longer lasting bubbles allow drinks to remain fresh tasting to the last drop.



3 CARBONATION

An exclusive in-line water mistifier reduces purified water into minute particles creating a fine, gentle mist that when infused with on-demand CO₂ molecules, results in longer lasting sparkling water.

Equal pressure from all 3 components results in a controlled carbonation system producing smaller bubbles, allowing for enhanced aromas, an effervescent mouth feel, and an explosion of flavors with every sip.




¹Filter performance based on regularly scheduled maintenance and filter replacement after 5,000 gallons in order for the product to perform as advertised.

ING WATER

4 ABSORPTION

BUNN refresh creates a delicate balance of purified, cold water and a precise "light" level of carbonation for optimal absorption of flavors and ingredients.

With the precise balance provided by BUNN refresh, purified water absorbs more aroma and flavor molecules, delivering a better taste profile – while remaining consistent throughout the day, regardless of your volume.





Develop customer appeal with snack and sparkling beverage pairings.



Water based offerings are popular throughout the entire day.



Increase profits and enhance your menu with hand crafted destination beverages using natural, fresh ingredients.



Provide a superior and sustainable alternative to single-use bottled waters.

**SET THE STANDARD FOR
FLAVOR INFUSIONS AND LONGER
LASTING CARBONATION**



**BRINGING NATURAL
BACK TO WATER**

MODELS

BUNN refresh®



Counter Top System

DIMENSIONS & SPECS

- 26.5"D x 10"W x 27"H
- Power: 120V 15A circuit (NEMA 5-15P)
- Cooling Capacity: 5.6 Gal/hr before exceeding 41°F (75°F incoming water)
- Ice Bank Size: 8 lbs



Tower and Undercounter System

DIMENSIONS & SPECS

- Tower: 7.75"W x 14.5"D x 20.25"H, with 4.5" handles
- Undercounter System: 22"D x 20"W x 28"H
- Power: 120V 15A circuit (NEMA 5-15P)
- Cooling Capacity: 11.25 Gal/hr before exceeding 41°F (75°F incoming water)
- Ice Bank Size: 18 lbs

Product Number	Model	Finish	Temperature Setting °F	Gal/hr	Volts	Amps	Watts	Hertz	Agency
US Market									
45800.0000	Counter Top Push Button	Black/SS	40	5.6	120	4.5	540	60	ETL-Intertek NSF
45800.0001	Counter Top Portion Control	Black/SS	40	5.6	120	4.5	540	60	ETL-Intertek NSF
45800.0002	Counter Top Push Button	White/SS	40	5.6	120	4.5	540	60	ETL-Intertek NSF
45800.0003	Counter Top Portion Control	White/SS	40	5.6	120	4.5	540	60	ETL-Intertek NSF
45900.0100	Tower Pull and Hold	Satin Chrome/Black	40	11.2	120	6.0	720	60	ETL-Intertek NSF
45900.0101	Tower Portion Control	Satin Chrome/Black	40	11.2	120	6.0	720	60	ETL-Intertek NSF

Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting.

5020 Ash Grove Drive, Springfield, IL 62711 USA
 (800) 637-8606 | +1 (217) 529-6601 | www.bunn.com

