





A PATH TO GREAT ESPRESSO

GRIND, TAMP, BREW

Beans descend from the large 2.2lb (1kg) hopper into an internal grinder. High-quality precision burrs perform a clean-cut milling of the beans. A moment later, the coffee is tamped into a puck with precise dosage, and the brewing begins. Nine bar brew pressure used with a variable brew group creates rich, strong espresso.

MIXING

Engineered with three powder hoppers (two 3.3lb/1.5kg hoppers for larger demand flavors and a third 2.2lb/1kg hopper). Adjustable speed auger motors produce accurately portioned drink recipes.

TASTE

A highly efficient two-tank system (0.2gal/0.8L tank for espresso, and .75gal/2.84L tank for solubles) assures ideal serving temperatures for all espresso and café beverages.







Features

- 9 bar brew pressure used with a variable brew group to produce an excellent single or double shot with beautiful crema
- Tamping sensor achieves consistently great coffee extraction
- Precision burrs for clean-cut milling of the beans and assurance of superior grounds distribution
- Ideal serving temperature of espresso and café beverages are achieved with our independently controlled two tank system. Engineered with three powder hoppers: two 3.3lb (1.5kg) hoppers for the larger demand flavors and a third 2.2lb (1kg) hopper that allows for additional flavors
- Adjustable speed auger motors produce great consistency of ingredient portioning



Large hopper merchandises fresh coffee beans

Consumers can clearly see fresh whole beans in the large 2.2lb (1kg) hopper

Touchpad features easy, step-by-step selections

Touchpad has two programmable portion sizes from 8 to 12oz (230 to 350ml) and 9 cafe style beverage choices, plus hot water



MODELS											
Product Number	Model	Finish	Shots/hr	Volts	Amps	Watts	Hertz	Plug	Cord	Shipping Weight	Agency
U.S. Market											
44300.0201	Crescendo	Black/SS	40	120	15	1600	60	NEMA 5-15p	Yes	46.3kg (102lb)	NSF. Intertek
44300.0240	Crescendo	Black/SS	40	120/ 208-240	13.5 - 15.3	2800 - 3670	60	NEMA L14-20P	Yes	46.3kg (102lb)	NSF. One of the control of the contr
Canada Market											
44300.6201	Crescendo	Black/SS	40	120	11	1300	60	NEMA 5-15p	Yes	46.3kg (102lb)	NSF. of Intertek
Europe, Middle East, Africa (EMEA) Market											
44300.0200	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	EURO	Yes	46.3kg (102lb)	C€
44300.0213	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	UK	Yes	46.3kg (102lb)	C€
Middle Ea	st Market	:									
44300.0211	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	N/A	No	46.3kg (102lb)	KSA (€
Latin America (LATAM) Market											
44300.0212	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	N/A	No	46.3kg (102lb)	NSF O Intertek
Asia Pacific Market											
44300.0202	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	N/A	No	46.3kg (102lb)	C€
44300.0215	Crescendo	Black/SS	40	230	11.4 - 12.1	2500 - 2900	60	Korea 16A	Yes	46.3kg (102lb)	ктс
44300.0216	Crescendo	Black/SS	40	230	11.5 - 12.2	2500 - 2900	50	China 16A	Yes	46.3kg (102lb)	(€ China
44300.0218	Crescendo	Black/SS	40	220	11.5 - 12.2	2500 - 2900 525mm (3/8") ç	60		No	46.3kg (102lb)	(€ Taiwan

5020 Ash Grove Drive, Springfield, IL 62711 USA (800) 637-8606 | +1 (217) 529-6601 | www.bunn.com

