

nitron₂[®]
COLD DRAFT



Cold Brew and Nitro Coffee - On Tap

bunn.com/nitron

VARIETY OF CONFIGURATIONS

Nitron consistently dispenses Cold Brew without sacrificing quality. The keg-free design makes Nitron the ideal platform for delivering authentic Cold Brew taste without the need for a complex or lengthy brewing process. The Standard Nitron's two-tap design dispenses one Still and one Nitro-infused beverage. The All-Nitro model infuses micro-bubbles in both taps for a long-lasting, velvety smooth finish.

Cold Brew and Nitro



All-Nitro



All Nitro

Need more than one Nitro tap?
The All-Nitro model infuses beverages with micro-bubbles from both taps - enabling Nitron to quickly serve high volume demands.

QUALITY IN THE CUP



The Nitron Experience – No milk or sugar needed! The BUNN exclusive in-line nitro infuser produces up to 3 minutes* of cascading micro-bubbles, crowning your beverage with a stout-like head that tastes distinctively creamy and delivers a soft, velvety mouthfeel.

Proven Technology – Leveraging BUNN's consistent and reliable High Intensity® mixing chamber assures a perfectly blended finished beverage, cup-after-cup.



*Results based on product concentrate used

INVITING AND EASY TO USE

KEG FREE

Achieve a nitro infusion with no kegs to change-out, store, clean or sanitize! Uses one gallon concentrate BIBs or BUNN refillable containers that your staff is already familiar with. Each BIB yields 5 to 33 gallons of finished drinks.

ARTFUL STLYING

Chrome-plated brass tap handles and LED-lighted door graphics are sure to liven up your counterspace and grab customer attention.

NARROW FOOTPRINT

Cold Brew Coffee, Iced Coffee, or Iced Tea - all from a sleek 10-inch wide footprint.

GREAT DESIGN



The Nitron Experience

Smooth Cold Brew
Velvety Nitro Infusion

Reliably meet your high volume demand for quality cold brew. With Nitron, it's as easy as plug-and-pour.

MODELS AND SPECIFICATIONS

MATERIAL	Metal Housing and Stainless Steel
FLOW RATE	1.0oz - 1.5oz per second
GAS	Food-Grade Nitrogen Required
VENTILATION	6" Back and top
MINIMUM WATER INLET PRESSURE	30 PSI
MAXIMUM WATER INLET PRESSURE	90 PSI
WATER SUPPLY CONNECTION	3/8" MFL
N2 GAS INPUT CONNECTION	1/4" Male Flare Bulkhead
MINIMUM N2 INLET PRESSURE	120 PSI
MAXIMUM N2 INLET PRESSURE	130 PSI
ICE BANK	8 lbs
HIGH PRESSURE N2 REGULATOR (required for use with tanks)	125 PSI Maximum Output
	
Product #: 54060.0000	



Dimensions:

10" W x 28.4" D x 34" H
(254mm W x 721.36mm D x 863.6mm H)

Burst Capacity:

At a rate of one 12oz drink per minute, dispenses 60 drinks before exceeding 41°F (75°F incoming water)

DESCRIPTION				ELECTRICAL							SHIPPING	AGENCY
Product #	Model	Concentration Ratio	Ftment	Volts	Amps	Watts	Hertz	Phase	Plug	Cord Attached	Weight	Listing
51600.0000	Nitron Cold Draft Countertop	4:1 - 12:1	Ball Valve	120	4.5	540	60	1	NEMA 5-15p	Yes	130lbs (58.96kg)	NSF 
51600.0003	Nitron Cold Draft Countertop	10:1 - 32:1	Ball Valve	120	4.5	540	60	1	NEMA 5-15p	Yes	130lbs (58.96kg)	NSF 
51600.0011	Nitron All Nitro Cold Draft Countertop	4:1 - 12:1	Ball Valve	120	4.5	540	60	1	NEMA 5-15p	Yes	130lbs (58.96kg)	NSF 

Plumbing: 30-90 PSI. Machine supplied with 3/8" male flare fitting.

5020 Ash Grove Drive, Springfield, IL 62711 USA
(800) 637-8606 | +1 (217) 529-6601 | www.bunn.com

